






UPC Code: 07847702990

Country Of Origin: Mexico



8300-LIG

Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Hospital Grade, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire; pre-wired ground leadNEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Orange

Technical Information

AC Horsepower Ratings At Rated Voltage: 1 HP

Electrical Specifications Amperage: 20 A Current Limiting: Full Rated Current Dielectric Voltage: Withstands 2000V per UL498 Grounding: Self-Grounding Pole: 2 Temperature Rise: Max 30C after 250

Voltage: 125 VAC Wire: 3

Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40°C to 60°C

Material Specifications Body Material: Nylon Clamp Nuts: Zinc-Plated Steel Color: Orange Face Material: Nylon Ground Clips: Brass-Plated Grounding Screw: Brass 8-32 Line Contacts: Brass Triple-Wipe Strap Material: Steel Terminal Screws: Brass 10-32 Mechanical Specifications **Product ID:** Ratings are permanently marked on device

Terminal Accom.: 14-10 AWG Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral


Termination: Back or Side Wire; prewired ground lead

Product Features


Color: Orange Device Type: Duplex Receptacle Outlet Grade: Heavy-Duty Hospital Grade Grounding: Self-Grounding NEMA: 5-20R Function: Isolated Ground Feature 4: Smooth Face

Standards and Certifications ANSI: C-73 CSA C22.2 No. 42: File 152105 NEMA: WD-6 NOM: 057 UL498HG: File E13399 UL Fed Spec WC-596: File E13399 Warranty: 10 Year Limited

Dimensional Diagram



Wiring Diagram



5-20R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

