



UPC Code: 07847752559 Country Of Origin: Mexico

55208-ASA

Brand Features

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Item Description

Type 1 Surge Arrester, 3 Phase 120/208V WYE, or 3 Phase Delta 240V, UL 1449 3rd Ed. Polycarbonate Enclosure with UV Inhibitors.

Technical Information

Electrical Specifications Frequency: 50/60Hz

Surge Technology: TPMOV Voltage: 120/208 VAC

Environmental Specifications

Flammability: Rated V-2 per UL 94 Operating Temperature: -10°C to 60°C Storage Temperature: -20°C to 85°C

Material Specifications Enclosure: Polycarbonate with UV inhibitors

Mechanical Specifications

Connection Type: Parallel Connection: Hardwired via 10AWG wire Diagnostics: Protection Status LEDs & Audible Alarm Enclosure: Type 3R Performance Data

Maximum Surge Current, Per Mode (Per Phase): 50kA (50kA) MCOV: 150V

Nominal Discharge Current Rating: 20kA

Voltage Protection Rating (VPR) (Clamping) L-N/L-L: 600V/800V

Standards and Certifications

ANSI/IEEE Category C: C-62.11, C-62.41 & C-62.45

ETL Certified: UL 1449 3rd Ed, Type 1 Device

National Electric Code (NEC): 285

Warranty

Connected Equipment Coverage: Up to \$10,000

Product Warranty: Limited Lifetime

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	_
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

