

T5832-B





UPC Code: 07847776436
Country Of Origin: China

T5832-B

Brand Features

The Leviton USB Charger/Tamper-Resistant Duplex Receptacle offers two high-powered USB Ports with 3.6A of charging power and two 20A or 20A/125V Tamper-Resistant Receptacles. It has the capability to charge two USB powered electronic devices utilizing its two USB Ports, leaving the two Tamper-Resistant Receptacles free for other uses. The Leviton USB Charger/Tamper-Resistant Duplex Receptacle is designed to charge tablets, smart and mobile phones, gaming devices, e-readers, digital cameras and a host of other electronic devices.

Item Description

Combination Duplex Receptacle/Outlet and USB Charger. 20 Amp, 125 Volt, Decora Tamper-Resistant Receptacle/Outlet, NEMA 5-20R. 3.6 Amps, 5VDC, 2.0 Type A USB Chargers. Grounding, Side Wired & Back Wired - Brown

Technical Information

Electrical Specifications **Grounding:** Grounding

Receptacle Voltage: 125V AC Horsepower Rating: 20A-1 HP

Ratings: 20A-125V

Environmental Specifications

Operating Temperature: -10C to 40C **Flammability:** Rated V-0 per UL94

Material Specifications **Strap Material:** Steel

Body Material: Thermoplastic

Color: Brown

Cover Material: Thermoplastic

Mechanical Specifications

Product ID: Stamped on Strap

Terminal ID: Brass-Hot Black-Hot
White-Neutral Green-Gnd

Termination: Back & Side
Terminal Accom.: 14-12 AWG
Torque Range: 12-14 inch pounds

Product Features
Color: Brown

Amperage: 20 Amp **Grade:** Spec Grade

Standards and Certifications

Listed: cCSAus

FCC Part 15: Class B for Residential

Compliance

Warranty: 5 Year Limited

NOM: 057