



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 104840, Century® Cast Bronze SAE660 Sleeve Bearings / Bushings - INCH

Isostatic Century Bronze® Bearings / Bushings

- Standard stock products
- SAE 660 / CA 932-copper 83%, tin 7%, lead 7%, zinc 3%
- Longer length bar up to 105" available on made-to-order basis
- Non-porous, highly dense grain structure for long life
- Offers good hardness, strength and wear resistance; excellent anti-frictional characteristics
- Tensile strength of 35,000 psi, yield strength of 27,000 psi and brinell hardness of 72
- Ideal for heavy loads at moderate speeds or light loads at high speeds –

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

2 IN I.D. x 2-1/4 IN O.D. x 2-1/2 IN Length, SAE 660 Cast Bronze, Sleeve Bearing

Specifications

Catalog Number CB-3236-20

Interchange # CB 3236-20
CB323620

Unit of Measure Each

Material Cast Bronze

Material Standard SAE 660

Avg Unit Weight	0.6740 lb
UPC Code	00846802021498

Dimensions

Nominal Inner Diameter	2 in
Nominal Outer Diameter	2 1/4 in
Nominal Length	2 1/2 in

Tolerances

Inner Diameter Tolerance	±.001 in
Outside Diameter Tolerance	+.002 to +.003 in
Overall Length Tolerance	±.005 in

Performance Data

Load - P Max Value	3,000 lb/in ²
Speed - V Max Value	750 ft ² /min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	75,000