
Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 706034, TP® Lead Free Steel-Backed PTFE Lined Flange Bearings - METRIC

Isostatic TP® Flange Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
  - Low carbon steel backing for extremely high load capacity - .50 – 2.7 mm thick
  - Sintered bronze offers optimal heat dispersion – .20 - .35 mm thickness and
  - PTFE – lead free sliding surface creates a low friction coefficient and allows for a wide temperature range – thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well with

+ more



Description | Specifications | Dimensions | Tolerances | Performance Data

Description

Detailed Description	35 MM I.D. x 39 MM O.D. x 26 MM Length, TP, Lead Free Steel Back, PTFE Lined Composite, Flange Bearing, Metric

Specifications

Catalog Number	FM3526TP
Interchange #	BB3526DP4 EGF35260-E40
Unit of Measure	Each
Material	Lead Free Steel-Backed PTFE
Material Standard	Lead Free Steel-Backed PTFE

Avg Unit Weight	0.1153 lb
UPC Code	00846802081669

Dimensions

Nominal Inner Diameter	35 mm
Nominal Outer Diameter	39 mm
Nominal Length	26 mm
Flange Nominal Outer Diameter	47 mm
Flange Nominal Thickness	2 mm
Recommended Housing Bore	39.000 to 39.025 mm
Recommended Shaft Size	34.950 to 34.975 mm

Tolerances

Overall Length Tolerance	±.25 mm
Flange Diameter Tolerance	±.50 mm
Flange Thickness Tolerance	1.80 to 2.00 mm

Performance Data

Load - P Max Value	36,250 lb/in²
Speed - V Max Value	1,900 ft²/min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000