


BLAZING SnapLOC

Filled Connectors for Outdoor/Electrical Use




INSTALLATION INSTRUCTIONS


IMPORTANT: Turn off power before installing or removing connector. Product to be used in accordance with local and national codes.



1. Strip wires to 11/16". Use one of the strip guides molded into the connector for reference. Pre-twist stranded wires.



2. Rotate handles fully apart beyond 90 degrees. Insert stripped wires into connector; #12-#14 in the large holes and #16-#20 in the small hole. Exposed ends of wires should be visible through the clear housing on the back.



3. Hold wires in place while squeezing handles together until the latch snaps shut.

BVS2 Waterproof Connectors

SKU #	Selling Unit
BVS2	Bag of 20

PRODUCT SPECIFICATIONS & MEASUREMENTS

Max. Voltage: 30V Max. building wire

Connector Size: 1.922" x 1.522"

Wire Type: Copper/Copper

Wire Range: Large Hole Min #14/Max #12

Small Hole Min #20/Max #16

Temperature Rating: 105°C (221°F)



Silicone Sealant Temperature: -40°F to 400°F

Measurements:

A - 1.922"

B - 1.522"

C - 1.355"



Selected 30V Wire Combinations
For use with solid and/or stranded combinations.

Large Hole Min #14/Max #12

Small Hole Min #20/Max #16

Contact factory for a complete list of wire combinations at 800.633.0232.

KING
INNOVATION®

U.S. Pat. 7,335,050, D575,738, D575,230, and
other patents pending.
50100-118 REV B 07/19

www.kinginnovation.com
(P) 800.633.0232
(F) 636.519.5410