



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 104030, Century® Cast Bronze SAE660 Sleeve Bearings / Bushings - INCH

Isostatic Century Bronze® Bearings / Bushings

- Standard stock products
- SAE 660 / CA 932-copper 83%, tin 7%, lead 7%, zinc 3%
- Longer length bar up to 105" available on made-to-order basis
- Non-porous, highly dense grain structure for long life
- Offers good hardness, strength and wear resistance; excellent anti-frictional characteristics
- Tensile strength of 35,000 psi, yield strength of 27,000 psi and brinell hardness of 72
- Ideal for heavy loads at moderate speeds or light loads at high speeds –

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

3/8 IN I.D. x 9/16 IN O.D. x 3/4 IN Length, SAE 660 Cast Bronze, Sleeve Bearing

Specifications

Catalog Number	CB-0609-06
Interchange #	CB 0609-06 CB060906
Unit of Measure	Each
Material	Cast Bronze
Material Standard	SAE 660

Avg Unit Weight	0.0330 lb
UPC Code	00846802013394

Dimensions		—
Nominal Inner Diameter	3/8 in	
Nominal Outer Diameter	9/16 in	
Nominal Length	3/4 in	

Tolerances		—
Inner Diameter Tolerance	±.001 in	
Outside Diameter Tolerance	+.002 to +.003 in	
Overall Length Tolerance	±.005 in	

Performance Data		—
Load - P Max Value	3,000 lb/in²	
Speed - V Max Value	750 ft²/min	
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	75,000	