

## **Isostatic Industries, Inc.** 4153 North Kostner Avenue

Chicago, IL 60641 Toll Free: 800.621.5500 Phone: 773.286.3444

Fax: 773.282.3323 Email: info@isostatic.com

## Item # 506004, TP® Lead Free Steel-Backed PTFE Lined Flange Bearings - INCH

## Isostatic TP® Flange Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
  - ∘ Low carbon steel backing for extremely high load capacity .50 2.7 mm thick
  - Sintered bronze offers optimal heat dispersion .20 .35 mm thickness and
  - o PTFE lead free sliding surface creates a low friction coefficient and allows for a wide temperature range thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well with



+ more

## <u>Description</u> | <u>Specifications</u> | <u>Dimensions</u> | <u>Tolerances</u> | <u>Performance Data</u>

Description		-
Detailed Description	.375 IN I.D. x .4688 IN O.D. x 0.7500 IN Length, TP, Lead Free Steel Back, PTFE Lined Composite, Flange Bearing	

Specifications		-
Catalog Number	06FTP12	
Interchange #	06FDP412	
Unit of Measure	Each	
Material	Lead Free Steel-Backed PTFE	
Material Standard	Lead Free Steel-Backed PTFE	

Avg Unit Weight	0.0144 lb
UPC Code	00846802079130

Dimensions	-
Nominal Inner Diameter	3/8 in
Nominal Outer Diameter	15/32 in
Nominal Length	3/4 in
Flange Nominal Outer Diameter	11/16 in
Flange Nominal Thickness	3/64 in
Recommended Housing Bore	.4684 to .4694 in
Recommended Shaft Size	.3731 to .3740 in

Tolerances		-
Overall Length Tolerance	±.01 in	
Flange Diameter Tolerance	±.02 in	
Flange Thickness Tolerance	.044 to .052 in	

Performance Data		-
Load - P Max Value	36,250 lb/in²	
Speed - V Max Value	1,900 ft²/min	
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000	