



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 502413, TU® Steel-Backed PTFE Lined Thrust Washers - INCH

Isostatic TU® Thrust Washer Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
 - Low carbon steel backing for extremely high load capacity-.50 – 2.7mm thick
 - Sintered bronze offers optimal heat dispersion –.20 - .35 mm thickness and
 - PTFE – lead sliding surface creates a low friction coefficient and allows for a wide temperature range – thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well with

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

1.5 IN I.D. x 2.5 IN O.D. x 0.061 IN Thickness, TU, Steel Back, PTFE & Pb Lined Composite, Thrust Washer Bearing

Specifications

Catalog Number	W22TU
Interchange #	DU22 G22DU
Unit of Measure	Each
Material	Steel-Backed PTFE Lined
Material Standard	Steel-Backed PTFE Lined

Avg Unit Weight	0.0473 lb
UPC Code	00846802058371

Dimensions

Nominal Inner Diameter	1 1/2 in
Nominal Outer Diameter	2 1/2 in
Nominal Thrust Washer Thickness	1/16 in
Nominal Dowel Hole Diameter	1/5 in
Nominal Dowel Hole Pitch Circle Diameter	2 in
Nominal Housing Recess Depth	1/16 in

Tolerances

Inner Diameter Tolerance	+0.010 in
Outside Diameter Tolerance	-0.010 in
Thrust Washer Thickness Tolerance	+0.0020 in
Dowel Hole Diameter Tolerance	+0.010 in
Dowel Hole Pitch Circle Diameter Tolerance	-0.010 in
Housing Recess Depth Tolerance	+0.010 in

Performance Data

Load - P Max Value	36,250 lb/in ²
Speed - V Max Value	1,900 ft ² /min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000