



Product Number: 23502

Order Abbreviation: F96T12/CWXSSCVP

General Description: 60W, 96 inch MOL, T12 instant start Slimline SUPER SAVER fluorescent lamp, Deluxe Cool White phosphor, 4100K color temperature, 87 CRI, customer value pack. VIVID Color: High CRI lamps for color critical applications.

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	F96T12CWXSSCVP 10/CS 10/SKU
Actual Length (in)	94.000
Actual Length (mm)	2387.60
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	87
Color Temperature/CCT (K)	4100
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	SuperSaver®
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	3850
Mean Lumens at 25C	3390
Nominal Length (in)	96.000
Nominal Length (mm)	2438.40
Nominal Wattage (W)	60.00
Outside Diameter (in)	1.593
Life at 3 hrs./start on IS ballasts	12000
Life at 12 hrs./start on IS ballasts	18800



Footnotes

- Recommended for use on one or two lamp high power factor, lead, instant-start, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 32 watt or 60 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.
- Mean lumens are measured at 40% of average rated lamp life.
- The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).

