



Pro Plus Line

Portable Fire Extinguishers



Pro Plus 2.5 MP Fire Extinguisher

Part number 468000

Multipurpose use

Rechargeable

UL Rated 1-A:10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro Plus 2.5 MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from impact resistant steel cylinder & sturdy aluminum valve assembly.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

At a Glance

- Model ProPlus 2.5 MP
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 1-A:10-B:C
- U.S.C.G, DOT approved
- Supplied with USCG approved retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Pt # 468000 - 6 pack
UPC: 0-47871-68000-9
I2F: 20047871680003

Product Specification

Net agent weight (Average)	2.6 lb.
Unit weight (Average)	4.38 lb.
Diameter	3.0 inches
Height	15.0 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	195 psi
Cylinder	Steel
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com

Pro Plus 5 MP Fire Extinguisher

Part number 468001

Multipurpose use

Rechargeable

UL Rated 3-A:40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro Plus 5 MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from impact resistant steel cylinder & sturdy aluminum valve assembly.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

At a Glance

- Model ProPlus 5 MP
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 3-A:40-B:C
- USCG, DOT approved
- Supplied with USCG approved retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Pt # 468001- 1 pack
UPC: 0-47871-68001-6
I2F: 20047871680010

Product Specification

Net agent weight (Average)	5 lb.
Unit weight (Average)	8.63 lb.
Diameter	4.25 inches
Height	15.0 inches
Discharge time	12-14 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Steel
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com

Pro Plus 10 MP Fire Extinguisher

Part number 468002

Multipurpose use

Rechargeable

UL Rated 4-A:80-B:C



For use on the following types of fire:



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro Plus 10 MP unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 10 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 18116

UPC: 0-47871-68002-3

At a Glance

- Model ProPlus 10 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 4-A:80-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Pt # 468002- 1 pack
UPC: 0-47871-68002-3
I2F: 20047871680027

Product Specification

Net agent weight (Average)	10 lb.
Unit weight (Average)	17.44 lb.
Diameter	5.25 inches
Height	19.13 inches
Discharge time	20-22 seconds
Discharge range	16-20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Metal
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com

Pro Plus 20 MP Fire Extinguisher

Part number 468003


Multipurpose use

Rechargeable

UL Rated 20-A:120-B:C



For use on the following types of fire:



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro Plus 20 MP unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 20 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 18117

At a Glance

- Model Pro Plus 20 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 20-A:120-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Pt # 468003- 1 pack
UPC: 0-47871-68003-0
I2F: 20047871680034

Product Specification

Net agent weight (Average)	20 lb.
Unit weight (Average)	31 lb.
Diameter	7.25 inches
Height	21.6 inches
Discharge time	26-28 seconds
Discharge range	16-20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Metal
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com

6 Liter Class K Wet Chemical Fire Extinguisher

Part number 25074

Cooking media

Rechargeable

UL Rated K



Description

Suitable for use on Class K cooking grease and oil fires.

The move toward more efficient cooking appliances and the widespread use of unsaturated cooking oils dictates the development and use of new types of portable fire extinguishers.

These wet chemical extinguishers are designed to deliver the agent safely on to the fire with a more gentle application. In addition the fire fighting agent has a greater fire fighting capacity and cooling effect on grease fires than dry chemical agents.

Features

- Safe and durable stainless steel cylinder
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 6 liter (1.6 gallons) of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Corrosion resistant cylinder & valve assembly

"Shipped Factory Filled"

For use on the following type of fire:



At a Glance

- Model WC-100 KS Pro
- Wet chemical
- UL listed
- UL rated K
- Potassium Acetate
- Supplied with wall hanger
- 6 year limited warranty

Pt # 25074 - 1 pack
UPC: Not Available
I2F: Not Available

Product Specification

Net agent weight (Average)	1.6 gallons (6 liters)
Unit weight (Average)	23.3 lb.
Diameter	7.0 inches
Height	19.5 inches
Discharge time	55-60 seconds
Discharge range	8-12 feet
Operating pressure	100 psi
Cylinder	Stainless steel
Valve, handle, lever	Brass & stainless steel

Packaging Options



SHIPPED IN CARTON

Packaging dimensions (inches)

	Depth	Width	Height
Carton	8.19	8.19	26.37



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com

Pro 2.5 W Water Fire Extinguisher

Part number 466403

Water

Rechargeable

UL Rated 2-A



Description

Suitable for use on Class A (trash, wood & paper) fires.

The Pro 2.5 W unit performs better, lasts longer, and offers the best value in the extinguisher industry and is the number one choice for virtually all hazards where class A-type materials may be present.

Features

- Safe and durable stainless steel cylinder
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2½ gallons of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Corrosion resistant cylinder & valve assembly

At a Glance

- Model Pro 2.5 W
- Water
- UL listed
- UL rated 2-A
- Supplied with wall hanger
- 6 year limited warranty

For use on the following types of fire:



Product Specification

Net agent weight (Average)	2½ gallons
Unit weight (Average)	32.5 lb.
Diameter	7.0 inches
Height	24.75 inches
Discharge time	55 seconds
Discharge range	30-45 feet
Operating pressure	100 psi
Cylinder	Stainless steel
Valve, handle, lever	Brass & stainless steel
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options

Pt # 466403 - 1 pack
UPC: 0-47871-66403-0
I2F - 10047871664037



SHIPPED IN CARTON

Packaging dimensions (inches)

	Depth	Width	Height
Carton	7.25	7.25	35.62



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com