UL Rated 2-A, 10-B:C









Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 210 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a tough aluminum valve assembly.

Features bilingual nameplate and carton.

> FOR LOW HAZARDS A 2-A:10-B:C rated extinguisher is required for protecting LOW

Features

- **Multipurpose Fire** Extinguisher
- Aluminum cylinder
- Tough aluminum valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable unit.
- Assembled in Mexico from global components.
- 6 year warranty
- UL rated 2-A, 10-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Optional metal strap bracket Pt # 466400
- Powder coated cylinder for corrosion protection



Pt # 21005779 - 4 pack UPC: 0-47871-05779-5 I2F - 10047871057792 Pt # **21007158 - 24** pack Lowe's UPC: 0-47871-05779-5 I2F - 20047871057799

For use on the following types of fire:









hazard occupancies such as: living areas of the home, offices, churches, assembly halls classrooms & hotel quest areas.

Product Specification

· · · · · · · · · · · · · · · · · · ·		L
Net agent weight (Average)	4 lb.	
Unit weight (Average)	7.5 lb.	
Diameter	4.5 inches	
Height	15.7 inches	
Discharge time	13-15 seconds	
Discharge range	10-15 feet]
Operating pressure	100 psi	
Cylinder	Seamless aluminum	IJ
Valve/handle/lever	Aluminum	
Strap Bracket (not supplied)	U.S.C.G approved	

Packaging Options



Packaging dimensions (inches)				
	Depth	Width	Height	
Carton	4.75	6.0	16.0	
Master Pack	13.0	17.25	9.87	

