

ProPlus 11 H Halotron Fire Extinguisher

Part number 466729

Clean agent

Rechargeable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids) and Class C fires (energized electrical equipment).

The ProPlus 11 H Halotron unit is environmentally safe and ideal for protecting delicate electronic equipment as the clean agent leaves no residue. The cylinder is manufactured from impact resistant steel and the valve assembly is metal.

The Halotron line is EPA approved and listed as an alternative to Halon 1211.

Features

- Agent will not cause thermal shock to electrical equipment
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 11 lb. of fire extinguishing agent (Average)
- 2 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection
- Optional metal retention bracket 23131

At a Glance

- Model ProPlus 11 H
- Halotron
- UL listed
- UL rated 1-A, 10-B:C
- Supplied with wall hanger
- 2 year limited warranty
- Suitable for use on energized electrical equipment

For use on the following types of fire:



Product Specification

Net agent weight (Average)	11 lb.
Unit weight (Average)	23.0 lb.
Diameter	7.25 inches
Height	16.18 inches
Discharge time	11 seconds
Discharge range	9-15 feet
Operating pressure	125 psi
Cylinder	Steel
Valve, handle, lever	Brass & stainless steel
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options

Pt # 466729 - 1 pack
UPC: 0-47871-66729-1
I2F: 20047871667295



SHIPPED IN CARTON

Packaging dimensions (inches)

	Depth	Width	Height
Carton	7.25	7.25	18.0



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com