



UPC Code: 07847747429

Country Of Origin: United States

26W10

20A-250V/ 10A-600V, Non-NEMA, 4P, 5W, Plug, Locking Blade, Industrial Grade, Non-Grounding, Wetguard - YELLOW

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

Technical Information

Electrical Specifications Grounding: Non-Grounding Amperage: 20/10 A Voltage: 250 VAC Pole: 4 Wire: 5 Dielectric Voltage: Withstands 2000V per UL498 Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current Environmental Specifications

Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C Environment: Wet

Material Specifications Body Material: Santoprene TPV

Compression Nut, Strain Relief: Nylon Body Interior: Nylon


Wire Module: Nylon

Bushing: Santoprene TPV

Blades/Contacts: Electroless Nickelcoated Brass

Terminal Screws: Electroless Nickelcoated Brass

Assembly Screws: Stainless Steel, Non-Magnetic



Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: #16 to #10 Product ID: Ratings and NEMA I.D. permanently marked on device

Cord Grip Range (in): .375-.875

Product Features Color: Yellow Brand: Wetguard Device Type: Locking Plug

Standards and Certifications NEMA: WD-6

ANSI: C-73 UL: 498 CSA C22.2 No. 42: File LR-406 NOM: 057 Warranty: Lifetime Warranty

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

