





UPC Code: 07847783832

3100R4W

100 Amp, 125 Volt, 2P, 3W, Outlet North American Pin & Sleeve Receptacle, Industrial Grade, IP67, Watertight - YELLOW

Technical Information

Electrical Specifications Amperage: 100 A

Current Interrupting: Certified for current interrupting at full rated current Dielectric Voltage: 2000V for 1 min. **Endurance:** Up to 250 connects and disconnects, under load, at full rated

current and voltage

Insulation Resistance: 500V for 1 min; >= 5M

Pole: 2

Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current

Voltage: 125 VAC

Wire: 3

Environmental Specifications

Corrosion Resistance: Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min

Flammability: Rated V-0 per UL 94

IP Rating: IP67/IP69K

Moisture Resistance: Per UL 1682, immersed for 24 hours in 5cm of 25°C

water

Material Specifications

Arm Spring: Performance Grade

Stainless Steel

Body Material: Valox 357

Cover Eyelet: Nickel-Plated Brass Cover with Arm: Valox 357 Gasket Material: Chloroprene Mounting Flange: Valox 357 Phase and Ground Sleeves: Brass Sleeve Spring: Stainless Steel Terminal Screws: Stainless Steel

Mechanical Specifications

Crush Test: 250lbs for 1 min after -25°C

Impact Resistance: Drop from 30" 8 times after conditioning to -25°C for 6 hrs Minimum Withdrawal Force: 20lbs

Product Features Color: Yellow

Configuration: North American Device Type: Receptacle


Standards and Certifications


CE Marking: Per low voltage directives 73/23/EEC, 93/68/EEC

CSA Certified: C22.2 No 182.1 IEC Rating: 60309-1 and 60309-2

UL Listed: 1682 and 1686 Warranty: 2-Year Limited

Dimensional Diagram





SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:templane} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

