



Proven Every Day // Proven Everywhere®



LEAK-TITE® Blue Thread Sealant With PTFE Resins

Economical Thread Sealant With PTFE

LEAK-TITE® Blue thread sealant contains PTFE particles for greater sealing power. With non-staining easy clean-up, it is ideal for use on production lines and fabrication shops.

FEATURES:

- Contains PTFE particles for greater sealing power
- Will not harden or dry out over time; remains flexible for easy disassembly
- Non-toxic, contains no solvents
- Sticks to hot, oily threads
- Ideal for use on production lines and fabrication shops
- Easy clean-up, will not stain hands or clothing
- Sealing temperature: -50°F to 500°F (-45°C to 260°C)
- Pressures to 1,500 PSI (102 BAR) for gas to 5,000 PSI (340 BAR) for liquid

TYPICAL APPLICATIONS:

- All types of pipe threads: steel, brass, iron, and PVC, ABS, and CPVC plastic
- Recommended Services: water, steam, air, natural gas, refrigerants and ammonia. Not for use on oxygen service.

RECOMMENDED INDUSTRIES:

- Fire Sprinkler
- Air Conditioning/Refrigeration
- Commercial/Residential Building Maintenance
- Plumbing
- Chemical Processing Plants

ORDERING INFORMATION:

Part No.	Size	Qty./Case	Wt. Lbs./Case
46009	1/4 pt. BIC	24	13
46019	1/2 pt. BIC	24	22
46029	1 pt. BIC	24	45.71
46013	1 qt.	12	41.30
46049	1 qt. BIC	12	42.47
46014	1 gal.	4	49.24
46015	5 gal.	1	65
40669	55 gal.	1	664

BIC=Brush In Cap



FBC™ System Compatible.
FBC™ is a trademark of the Lubrizol Corporation. Visit fbcsystemcompatible.com for additional information.



Call, write or email for additional information

LA-CO Industries Inc.
1201 Pratt Boulevard
Elk Grove Village, Illinois 60007-5746
1-800-621-4025 • 1-847-956-7600 • Fax: 1-800-448-5436
www.laco.com
Email: customer_service@laco.com
Family owned and operated since 1934