



UPC Code: 07847778673

# 1223-PLG

20 Amp, 120 Volt, Toggle Pilot Light - Illuminated ON - Req. Neutral 3-Way AC Quiet Switch, Extra Heavy Duty Spec Grade, Self Grounding, Back & Side Wired, - Green

Leviton's Industrial Grade AC toggle switches for extra heavy-duty applications represent top-of-the-line quality and peak performance. Leviton uses the finest materials available and the highest production standards to produce industrial switches of unmatched versatility and reliability.

#### **Technical Information**

AC Horsepower Ratings HP Rating: 1HP-120V Max. Amperage: 16 Amp

**Electrical Specifications** 

Amperage: 20 A Voltage: 120 VAC

Grounding: Self-Grounding Dielectric Voltage: Withstands 1500V for 1 minute

**Overload UL20 Test:** 100 cycles of OL at 4.8 times rated current

Temperature Rise: Maximum 30 degrees C rise

Endurance: 50,000 cycles minimum

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 65°C

Material Specifications Strap Material: .048" Thick Galvanized

Steel

Base Material: Thermoplastic Toggle: Polycarbonate Cover Material: Thermoplastic Contact Material: Silver Alloy Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Ground Clips: Brass Color: Green Mechanical Specifications

**Terminal ID:** Brass-Hot Black-Hot White-Neutral Green-Gnd

Terminal Accom.: 14-#10 AWG back wired; #14-#12 AWG side wired

**Product ID:** Ratings are permanently marked on device

Torque Range: 12-14 inch pounds Termination: Back or Side Wire

Product Features Color: Green

Function: 3-Way


**Grade:** Extra Heavy-Duty Industrial Specification Grade

Feature 2: Illuminated - Load ON (Pilot Light)

Device Type: Toggle Switch

Standards and Certifications


NEMA: WD-1 & WD-6 ANSI: C-73 UL Fed Spec WS896E: File #E7458 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 RoHS: Compliant Warranty: 10 Year Limited



# 3-WAY

# Wiring Diagram

3-Way Pilot Light



## SPECIFICATION SUBMITTAL

| JOB NAME:   | CATALOG NUMBERS: |
|-------------|------------------|
|             |                  |
| JOB NUMBER: |                  |

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

