

Product Number: 20819

Order Abbreviation: F8T5/SW/BL/1/6

General Description: 8W, 12" MOL, T5, preheat fluorescent lamp with miniature bi-pin bases, soft white phosphor, 3000K color temperature, 52 CRI, blister pack, 6 per case, 1 per SKU

Product Information

Abbrev. With Packaging Info.	F8T5SWBL16 6/CS 1/SKU
Actual Length (in)	11.909
Actual Length (mm)	302.49
Average Rated Life (hr)	7500
Base	Miniature Bipin
Bulb	T5
Color Temperature/CCT (K)	3000
Diameter (in)	0.630
Diameter (mm)	16.00
Initial Lumens at 25C	400
Nominal Length (in)	12.000
Nominal Length (mm)	304.80
Nominal Wattage (W)	8.00

Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Preheat lamp, starter required.
- Mean lumens are measured at 40% of average rated lamp life.
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).