



Product Number:

74509

Order Abbreviation:

HIBAY1A/100HUV840/GR

General Description:

High Bay 1A, 100 watts, 347-480V, 0-10V dimmable, 4000K, gray painted finish

Product Information

Diameter (in)	7
Diameter (mm)	177.8
Power Factor	0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	20 %
Efficacy (LPW)	108
Abbrev. With Packaging Info.	HIBAY1A100HUV840GR 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	HIBAY1A/100HUV840/GR
Average Rated Life 1 (hr)	63000
Lumens	10800
Nominal Voltage (V)	347.00
Nominal Wattage (W)	100.00
UPC Code	UPC046135745096
Color Rendering Index (CRI)	>80
Service Life Rating	63000
Lumens (lm)	10800
Wattage (W)	100.00
Accessories	Hook
Color Range	4000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Gray
Luminaire Type	High bay
Maximum Operating Temperature-Celsius	50
Maximum Operating Temperature-Fahrenheit	122
Power Input	100
Mounting	Suspended
Dimensions	7x13.4
Certification Listing	cULus, FCC, RoHS, DLC

