



**Product Number:** 64966

**Order Abbreviation:** MC150T7.5/U/G12/940

**General Description:** METALARC POWERBALL 150W ceramic metal halide tubular T7.5, clear, universal operation, G12 base, 4200K CCT, 95 CRI, pulse start, enclosed rated, 15,000 hour rated life

#### Product Information

Abbrev. With Packaging Info.	MC150T7.5UG12940 12/CS 1/SKU
ANSI Code	C142/E
ANSI Code 2	C142/E
Approx. Lumens (initial - horizontal)	14700
Approx. Lumens (initial - vertical)	14500
Approx. Lumens (mean - horizontal)	11600
Approx. Lumens (mean - vertical)	11600
Base	G12
Bulb	T7.5
Color Rendering Index (CRI)	95
Color Temperature/CCT (K)	3950
Diameter (in)	0.945
Diameter (mm)	24.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Maximum Base Temperature - Fahrenheit	536
Maximum Bulb Temperature - Fahrenheit	1112
Maximum Overall Length - MOL (in)	4.125
Maximum Overall Length - MOL (mm)	105
Nominal Voltage (V)	92.00
Nominal Wattage (W)	150.00
Operating Position	Universal



#### Footnotes

- Consult your LEDVANCE Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaires. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- UV-Stop quartz
- Lamps may be operated on a M142 Compliant ballast.
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.

