

IMAGE  
COMING  
SOON

|                      |                    |
|----------------------|--------------------|
| Product Number:      | 51516              |
| Order Abbreviation:  | OTDIM              |
| General Description: | LED Dimming Module |

Product Information

|                                   |                   |
|-----------------------------------|-------------------|
| Abbrev. With Packaging Info.      | OTDIM 20/CS 1/SKU |
| Ballast Factor                    | 1.00              |
| Ballast Height H (in)             | 0.7870            |
| Ballast Length L (in)             | 6.7720            |
| Ballast Width W (in)              | 1.6540            |
| Family Brand Name                 | OPTOTRONIC        |
| Input Current (Amps)              | 0.00              |
| Nominal Voltage (V)               | 10-24V            |
| Open Circuit Voltage (V)          | 10.5/24V          |
| Power Factor                      | 1                 |
| Sound Rating                      | A                 |
| Starting Temperature - Fahrenheit | -4                |
| Starting Temperature - Celsius    | -20               |
| Total Harmonic Distortion (THD)   | 99%               |
| Wiring Method                     | CONNECTORS        |



Footnotes

- UL508 recognized
- Install in accordance with National Electric Codes
- Minimum Starting Temperature: -4F/-20C.
- Data shown is at full light output.