# 1221-7PC



## UPC Code: 07847724063

Country of Origin: Please Contact Customer Service

# **Switches**

### **Brand Features**

Leviton's Industrial Grade AC toggle switches for extra heavy-duty applications represent top-of-the-line quality and peak performance. Leviton uses the finest materials available and the highest production standards to produce industrial switches of unmatched versatility and reliability.

### **Item Description**

20 Amp, 277 Volt, Toggle Pilot Light - Illuminated ON - Req. Neutral Single-Pole AC Quiet Switch, Industrial Grade, Self Grounding, Back & Side Wired, - Clear

### **Technical Information**

AC Horsepower Ratings HP Rating: 1HP-120V

Max. Amperage: 16 Amp

### **Electrical Specifications**

Amperage: 20 Amp Voltage: 277 Volt Grounding: Self-Grounding Dielectric Voltage: Withstands 1500V for 1 minute Overload UL20 Test: 100 cycles of OL at 4.8 times rated current Temperature Rise: Maximum 30 degrees

C rise

Endurance: 50,000 cycles minimum

# Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40°C to 65°C

Material Specifications Strap Material: .048" Thick Galvanized Steel

Base Material: Thermoplastic Toggle: Polycarbonate Cover Material: Thermoplastic Contact Material: Silver Alloy Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Ground Clips: Brass Color: Clear Mechanical Specifications

Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd

Terminal Accom.: 14-#10 AWG back wired; #14-#12 AWG side wired

Product ID: Ratings are permanently marked on device

Torque Range: 12-14 inch pounds

## Product Features


Color: Clear Grounding: Self Grounding Feature: Pilot Light - Illuminated ON -Req. Neutral HP Rating: 2HP-277V Actuator Material: Polycarbonate Body Material: Thermoplastic Strap Material: Steel

## Standards and Certifications


NEMA: WD-1 & WD-6 ANSI: C-73 UL Fed Spec WS896E: File #E7458 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 RoHS: Compliant Warranty: 10 Year Limited



# **Dimensional Diagram**



Wiring Diagram Single-Pole Pilot



# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc. 201 North Service Road, Melville, NY 11747 Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd. 165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V. Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com © 2012-2013 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence. If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

