



UPC Code: 07847795907

Country Of Origin: Mexico

3848-DIN

Brand Features

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Item Description

48 Volt DC, 2 Pole, 2 Wire, Equipment Cabinet SPD Surge Protective Device, Wired-In Module, DIN-Rail Mounted, Terminal Block Wired, in a NEMA 1 Enclosure

Technical Information

Environmental Specifications

Operating Temperature: -10°C to 60°C

Storage Temperature: -20°C to 85°C

Relative Humidity: 20% to 90% non-condensing

Altitude: 15,000 ft

Material Specifications

Case Material: Polycarbonate

DIN-Rail Material: Polycarbonate

Performance Data

Maximum DC Operating Voltage: 52.8V

Breakdown Voltage 100V/sec: 51.8 - 71.8 V

Maximum Surge Current 10 x 1000sec: 10A

Maximum Capacitance: 4.8f

UL497B Clamping: 71V

Product Features

Voltage: 48 VDC

Pole: 2

Wire: 2

Type: Wired-In Module

Diagnostics: LED

Mounting Type: DIN-Rail

Wiring: Terminal Block

Joules Rating: 280

MCOV: 52.8V DC

UL1449 Impulse Perm Wired Test L-N/L-G/N-G: /62/

Noise Rejection: -35 dB at 5kHz-5MHz

Circuitry: MOV-Based Suppression

Enclosure Rating: NEMA 1

Standards and Certifications: UL1449 / CSA / ANSI/IEEE Cat ABC

Warranty: 10 Year Limited

Standards and Certifications

UL: 497B Listed

CSA: C22.2

Product Warranty: 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

