

Compression F-Connector

APPLICATION

The Leviton Compression F-Connector is used in video applications such as CATV and satellite. Its radial-compression design provides a more secure termination on Series 6 Quad Shield Cable than the traditional hex-crimp design. For fast installation, terminate using the Leviton installer-friendly Master Compression Tool.



SPECIFICATION

The Compression F-Connector shall be constructed with brass and a tin finish. It shall feature a radial-compression design, providing 360-degree electrical continuity. The connector shall be able to withstand greater than 40 lbs pull force and maintain ≤ -0.2 dB up to 1 GHz (typical). The return loss shall be ≥ -30 dB up to 1 GHz. The Compression F-Connector shall have RFI shielding of -85 dB (typical).

FEATURES

- Compatible with Leviton Master Compression Tool for fast termination of Series 6 Quad Shield Cable

DESIGN CONSIDERATIONS

- Includes plastic guide pin to determine when cable is properly seated inside the connector
- Comes in packs of 100 pieces

PHYSICAL SPECIFICATIONS

Dimensions:	See page two
Materials:	Tin-plated brass
Cable Applications:	< 20 lbs max insertion
Cable Interface:	> 40 lbs pull force
Insertion Loss:	≤ -0.2 dB up to 1 GHz typical
Return Loss:	≥ -30 dB up to 1 GHz typical
RFI Shielding:	-85 dB typical (60% bonded foil) > 70dB to 1GHz
Environmental Range:	-40 °F to 140 °F

COUNTRY OF ORIGIN


China

WARRANTY INFORMATION


For a copy of Leviton product warranties, visit www.leviton.com/warranty.

ELECTRONIC FILES

For CAD files, typical specs, or technical drawings (.DXF, .DWG), visit www.leviton.com.



End View



Side View

40985-CPF

PART NUMBERS

Description	Part No.
Compression F-Connector, 100-pack	40985-CPF



Leviton Network Solutions 2222 - 222nd St. SE Bothell, WA 98021-4416 tel 1-800-824-3005 tel +1-425-486-2222 appeng@leviton.com www.leviton.com	Asia / Pacific T +1.631.812.6228 E infoasean@leviton.com	Canada T +1.514.954.1840 E pcservice@leviton.com	Caribbean T +1.954.593.1896 E infocaribbean@leviton.com	China T +852.2774.9876 E infochina@leviton.com	Colombia T +57.1.743.6045 E infocolombia@leviton.com
	Europe T +44.0.1592.772124 E customerserviceeu@leviton.com	India / SAARC T +971.4.886.4722 E infoindia@leviton.com	Mexico T +52.55.5082.1040 E lsamarketing@leviton.com	Middle East & Africa T +971.4.247.9800 E lmeinfo@leviton.com	South Korea T +82.2.3273.9963 E infokorea@leviton.com