



UPC Code: 4

Country Of Origin: Mexico

16R29-U

Brand Features

Rhino-Hide Single Pole Cam-Type Receptacles are tough and reliable. They feature a UV-stabilized high performance TPV insulator that resists cracking and color fading, and a positive vibration-proof connection. They are available in 8 standard colors for easy phase identification. NOTE: A complete catalog number requires that you append the color suffix to the base number as follows: W (White), E (Black), H (Brown), R (Red), B (Blue), O (Orange), G (Green), Y (Yellow). For example, to order a white plug the catalog number would be 16R21-UW.

Item Description

16 Series Male Panel Receptacle, Cam-Type, 45-Degree, Threaded Stud Length-3/4", Taper Nose, Cable Range - #2 to 4/0 AWG, 400 Amp

Technical Information

Electrical Specifications

Max. Amperage: 400 Amp

Max. Voltage: 600 Volt

Material Specifications

Sleeve Material: Santroprene TPV Contact Material: Brass Strain Relief: Copper Wire Mechanical Specifications

Gender: Male

Connection Type: Threaded Stud

Cable Range: 2-4/0 AWG
Standards and Certifications
NEMA Rating: Type 3R

UL: 1691

SPECIFICATION SUBMITTAL

ı	JOB NAME:	CATALOG NUMBERS:
ı		
	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

 $\hbox{@ 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.}\\$

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

