





UPC Code: 07847706761

Country Of Origin: Mexico



67W82

20 Amp, 277/480 Volt 3-Phase Y, NEMA L22-20R, 4P, 5W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, Wetguard w/Cover - YELLOW

Technical Information

AC Horsepower Ratings At Rated Voltage: 5 HP

Electrical Specifications

Current Limiting: Full Rated Current Dielectric Voltage: Withstands 2000V per UL498

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications Environment: Wet Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications
Base Material: Nylon

Face Material: Nylon

Grounding Screw: Nickel-Plated Brass 8-32

Line Contacts: Nickel-Plated Brass .040 Thick

Terminal Screws: Nickel-Plated Brass 10-32

Yoke: Nickel-Plated Brass .050 Thick


Mechanical Specifications **Product ID:** Ratings and NEMA I.D. permanently marked on device **Terminal Accom.:** 14-8 AWG

Terminal ID: Brass-Hot, Green-Ground, White-Neutral


Product Features

Amperage: 20 A Base Material: Nylon Brand: Wetguard Color: Yellow Face Material: Nylon Grounding: Grounding NEMA: L22-20R Pole: 4 Standards and Certifications: UL/CSA Strap Material: Nickel-Plated Brass Termination: Back Voltage: 277/480 VAC Warranty: Lifetime Warranty Wire: 5 Device Type: Locking Outlet Standards and Certifications ANSI: C-73 CSA C22.2 No. 42: File LR-406 NEMA: WD-6 NOM: 057 UL498: File E13399 UL Fed Spec WC-596: File E13399

Dimensional Diagram



Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30)

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

