



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 506401, TP® Lead Free Steel-Backed PTFE Lined Thrust Washers - INCH

Isostatic TP® Thrust Washer Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
 - Low carbon steel backing for extremely high load capacity - .50 – 2.7 mm thick
 - Sintered bronze offers optimal heat dispersion – .20 - .35 mm thickness and
 - PTFE – lead free sliding surface creates a low friction coefficient and allows for a wide temperature range – thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

.5 IN I.D. x .875 IN O.D. x 0.061 IN Thickness, TP, Lead Free Steel Back, PTFE Lined Composite, Thrust Washer Bearing

Specifications

Catalog Number	W06TP
Interchange #	DP406
Unit of Measure	Each
Material	Lead Free Steel-Backed PTFE
Material Standard	Lead Free Steel-Backed PTFE

Avg Unit Weight	0.0064 lb
UPC Code	00846802079437

Dimensions

Nominal Inner Diameter	1/2 in
Nominal Outer Diameter	7/8 in
Nominal Thrust Washer Thickness	1/16 in
Nominal Dowel Hole Diameter	1/15 in
Nominal Dowel Hole Pitch Circle Diameter	2/3 in
Nominal Housing Recess Depth	1/16 in

Tolerances

Inner Diameter Tolerance	+0.010 in
Outside Diameter Tolerance	-0.010 in
Thrust Washer Thickness Tolerance	+0.0020 in
Dowel Hole Diameter Tolerance	+0.010 in
Dowel Hole Pitch Circle Diameter Tolerance	-0.010 in
Housing Recess Depth Tolerance	+0.010 in

Performance Data

Load - P Max Value	36,250 lb/in ²
Speed - V Max Value	1,900 ft ² /min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000