



Rain & Repair Pipe Collar

UV Resistant • Fast & Easy Installation • No Mess Solution

IPS Corporation's Rain and Repair Collars are an economical solution that can be used on newly installed pipe vent flashings, creating a two-collar system to enhance the life of the roof flashing sealing collar. The second collar protects the main flashing seal from damaging UV rays and pipe movement, and provides a secondary water tight seal around the vent pipe. In addition, IPS Rain Collars can be used to instantly repair a leak on a weathered or damaged collar, until the flashing can be replaced.

To install an IPS Rain Collar:

- 1 Identify your pipe size and match to size printed on the top of the rain collar; then determine if a ring needs to be removed for proper fit when using multi-size collars
- 2 If removal of ring is required, use pliers to simply grab the tab adjacent to the pipe size required, push down to separate at the score, and then pull up to remove the ring
- 3 Slide the rain collar over the pipe on top of the existing new or leaking flashing



Scan QR code to view Rain & Repair
Pipe Collar installation video

RAIN & REPAIR PIPE COLLAR | Multi-Size Rain Collars



PRODUCT FEATURES

HIGHLIGHTS

- One collar fits multiple size pipes with use of pull tab
- Fully tested for ultraviolet, ozone & weather resistance

- Large size covers the entire existing elastomer collar
- Eliminates the need for a messy mastic or caulking repair job
- Protects the main flashing collar from UV damage
- Instantly repairs the elastomer sealing collar on all types of residential “no caulk” roof vent flashings
- Economical solution with a Limited Lifetime Warranty

PRODUCT	DESCRIPTION	MODEL	UPC	UNITS/CASE	LBS/CASE
81720	3 N 1® Rain Collar for 1 ¼”, 1 ½”, 2” or 3” Vent Pipe	RC31	012181-817209	20	5
81722	Collar for 3” or 4” Vent Pipe	RC34	012181-817223	20	5

RAIN & REPAIR PIPE COLLAR | Standard Size Rain Collars



PRODUCT FEATURES

HIGHLIGHTS

- Each collar fits only one pipe size
- Fully tested for ultraviolet, ozone & weather resistance

- Large size covers the entire existing elastomer collar
- Eliminates the need for a messy mastic or caulking repair job
- Protects the main flashing collar from UV damage
- Instantly repairs the elastomer sealing collar on all types of residential “no caulk” roof vent flashings
- Economical solution with a Limited Lifetime Warranty

PRODUCT	DESCRIPTION	MODEL	UPC	UNITS/CASE	LBS/CASE
81725	Collar for 1 ¼” or 1 ½” Vent Pipe	RC1	012181-817254	100	15
81730	Collar for 2” Vent Pipe	RC2	012181-817308	100	15
81735	Collar for 3” Vent Pipe	RC3	012181-817353	75	16
81740	Collar for 4” Vent Pipe	RC4	012181-817407	75	16
81745	Collar for ½”, ¾”, 1” Vent Pipe/25 bag	RC5	012181-817452	100	16