1/11/2018 Product Details

Product 25126

**Number:** 

Order F60T12/CW/HO

Abbreviation:

General 75W, 60"MOL, T12 HO (800 mA) rapid start fluorescent lamp, Cool White

Description: phosphor, 4200K color temperature, 60 CRI



\* Full Case Required

## **Product Information**

Abbrev. With Packaging Info. F60T12CWHO 30/CS 1/SKU

Actual Length (in) 57.720
Actual Length (mm) 1466.09
Average Rated Life (hr) 12000

Base Recessed Double Contact

 Bulb
 T12

 Color Rendering Index (CRI)
 60

 Color Temperature/CCT (K)
 4200

 Diameter (in)
 1.593

 Diameter (mm)
 40.46

Industry Standards ANSI C78.81 - 2001

 Initial Lumens at 25C
 5200

 Mean Lumens at 25C
 4212

 Mean Lumens at 35C
 4212

 Nominal Length (in)
 60.000

 Nominal Length (mm)
 1524.00

 Nominal Wattage (W)
 75.00

## **Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.