

## ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer



Ahmed Eissa

## ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer

### Key Features and Benefits



#### Applications

- Offices
- Retail Spaces
- Multipurpose Rooms
- Hospitality Areas

- Application : The ValueLED Retrofit Doorkit and Volumetric Troffer are offered in three sizes (1'x4', 2'x2', and 2'x4'). The addition of the 1'x4' options fills an existing gap in our current portfolio
- All models are DLC Premium listed to maximize rebate opportunities
- The lumen selectability feature allows for a wide range of lumen output options with fewer NAEDs, reducing the complexity of inventory management

| Dimensions | Wattage       | CCT                 | Lumens              | Warranty |
|------------|---------------|---------------------|---------------------|----------|
| 1x4        | 20, 25, or 30 | 3500, 4000, or 5000 | 2500, 3125, or 3750 | 5 years  |
| 2x2        | 20, 25, or 30 | 3500, 4000, or 5000 | 2500, 3125, or 3750 | 5 years  |
| 2x4        | 25, 30, or 34 | 3500, 4000, or 5000 | 3100, 3750, or 4250 | 5 years  |
| 2x4        | 34, 38, or 45 | 3500, 4000, or 5000 | 4250, 4750, 5600    | 5 years  |



# ValueLED™ Lumen Selectable Retrofit Doorkit

## Product Offering

| Item Number | Ordering Abbreviation                          | Wattage      | Voltage | Dimming | CRI/CCT | Lumens             | LPW | Lifetime | Option |
|-------------|------------------------------------------------|--------------|---------|---------|---------|--------------------|-----|----------|--------|
| 61525       | <a href="#">RDORKIT5AS/030UNVD835/22U/WH</a>   | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61526       | <a href="#">RDORKIT5AS/030UNVD840/22U/WH</a>   | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61527       | <a href="#">RDORKIT5AS/030UNVD850/22U/WH</a>   | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61528       | <a href="#">RDORKIT5AS/034UNVD835/24U/WH</a>   | 25, 30 or 34 | 120-277 | 0-10    | 835     | 3100, 3750 or 4250 | 125 | ≥50,000  | -      |
| 61529       | <a href="#">RDORKIT5AS/034UNVD840/24U/WH</a>   | 25, 30 or 34 | 120-277 | 0-10    | 840     | 3100, 3750 or 4250 | 125 | ≥50,000  | -      |
| 61530       | <a href="#">RDORKIT5AS/034UNVD850/24U/WH</a>   | 25, 30 or 34 | 120-277 | 0-10    | 850     | 3100, 3750 or 4250 | 125 | ≥50,000  | -      |
| 61531       | <a href="#">RDORKIT5AS/045UNVD835/24U/WH</a>   | 34, 38 or 45 | 120-277 | 0-10    | 835     | 4250, 4750 or 5600 | 125 | ≥50,000  | -      |
| 61532       | <a href="#">RDORKIT5AS/045UNVD840/24U/WH</a>   | 34, 38 or 45 | 120-277 | 0-10    | 840     | 4250, 4750 or 5600 | 125 | ≥50,000  | -      |
| 61533       | <a href="#">RDORKIT5AS/045UNVD850/24U/WH</a>   | 34, 38 or 45 | 120-277 | 0-10    | 850     | 4250, 4750 or 5600 | 125 | ≥50,000  | -      |
| 61534       | <a href="#">RDORKIT5AS/030UNVD835/14U/WH</a>   | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61535       | <a href="#">RDORKIT5AS/030UNVD840/14U/WH</a>   | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61536       | <a href="#">RDORKIT5AS/030UNVD850/14U/WH</a>   | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61696       | <a href="#">RDORKIT5AS/030UNVD835/22U/WH/E</a> | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61697       | <a href="#">RDORKIT5AS/030UNVD840/22U/WH/E</a> | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61698       | <a href="#">RDORKIT5AS/030UNVD85/022U/WH/E</a> | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61699       | <a href="#">RDORKIT5AS/034UNVD835/24U/WH/E</a> | 25, 30 or 34 | 120-277 | 0-10    | 835     | 3100, 3750 or 4250 | 125 | ≥50,000  | E      |
| 61700       | <a href="#">RDORKIT5AS/034UNVD840/24U/WH/E</a> | 25, 30 or 34 | 120-277 | 0-10    | 840     | 3100, 3750 or 4250 | 125 | ≥50,000  | E      |
| 61701       | <a href="#">RDORKIT5AS/034UNVD850/24U/WH/E</a> | 25, 30 or 34 | 120-277 | 0-10    | 850     | 3100, 3750 or 4250 | 125 | ≥50,000  | E      |
| 61702       | <a href="#">RDORKIT5AS/045UNVD835/24U/WH/E</a> | 34, 38 or 45 | 120-277 | 0-10    | 835     | 4250, 4750 or 5600 | 125 | ≥50,000  | E      |
| 61703       | <a href="#">RDORKIT5AS/045UNVD840/24U/WH/E</a> | 34, 38 or 45 | 120-277 | 0-10    | 840     | 4250, 4750 or 5600 | 125 | ≥50,000  | E      |
| 61704       | <a href="#">RDORKIT5AS/045UNVD850/24U/WH/E</a> | 34, 38 or 45 | 120-277 | 0-10    | 850     | 4250, 4750 or 5600 | 125 | ≥50,000  | E      |
| 61705       | <a href="#">RDORKIT5AS/030UNVD835/14U/WH/E</a> | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61706       | <a href="#">RDORKIT5AS/030UNVD840/14U/WH/E</a> | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61707       | <a href="#">RDORKIT5AS/030UNVD850/14U/WH/E</a> | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |



## ValueLED™ Lumen Selectable Volumetric Troffer

### Product Offering

| Item Number | Ordering Abbreviation                | Wattage      | Voltage | Dimming | CRI/CCT | Lumens             | LPW | Lifetime | Option |
|-------------|--------------------------------------|--------------|---------|---------|---------|--------------------|-----|----------|--------|
| 61512       | <u>VOLUME5AS/030UNVD835/22U/WH</u>   | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61513       | <u>VOLUME5AS/030UNVD840/22U/WH</u>   | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61514       | <u>VOLUME5AS/030UNVD850/22U/WH</u>   | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61515       | <u>VOLUME5AS/034UNVD835/24U/WH</u>   | 25, 30 or 34 | 120-277 | 0-10    | 835     | 3100, 3750 or 4250 | 125 | ≥50,000  | -      |
| 61516       | <u>VOLUME5AS/034UNVD840/24U/WH</u>   | 25, 30 or 34 | 120-277 | 0-10    | 840     | 3100, 3750 or 4250 | 125 | ≥50,000  | -      |
| 61517       | <u>VOLUME5AS/034UNVD850/24U/WH</u>   | 25, 30 or 34 | 120-277 | 0-10    | 850     | 3100, 3750 or 4250 | 125 | ≥50,000  | -      |
| 61518       | <u>VOLUME5AS/045UNVD835/24U/WH</u>   | 34, 38 or 45 | 120-277 | 0-10    | 835     | 4250, 4750 or 5600 | 125 | ≥50,000  | -      |
| 61519       | <u>VOLUME5AS/045UNVD840/24U/WH</u>   | 34, 38 or 45 | 120-277 | 0-10    | 840     | 4250, 4750 or 5600 | 125 | ≥50,000  | -      |
| 61520       | <u>VOLUME5AS/045UNVD850/24U/WH</u>   | 34, 38 or 45 | 120-277 | 0-10    | 850     | 4250, 4750 or 5600 | 125 | ≥50,000  | -      |
| 61521       | <u>VOLUME5AS/030UNVD835/14U/WH</u>   | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61522       | <u>VOLUME5AS/030UNVD840/14U/WH</u>   | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61523       | <u>VOLUME5AS/030UNVD850/14U/WH</u>   | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | -      |
| 61684       | <u>VOLUME5AS/030UNVD835/22U/WH/E</u> | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61685       | <u>VOLUME5AS/030UNVD840/22U/WH/E</u> | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61686       | <u>VOLUME5AS/030UNVD850/22U/WH/E</u> | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61687       | <u>VOLUME5AS/034UNVD835/24U/WH/E</u> | 25, 30 or 34 | 120-277 | 0-10    | 835     | 3100, 3750 or 4250 | 125 | ≥50,000  | E      |
| 61688       | <u>VOLUME5AS/034UNVD840/24U/WH/E</u> | 25, 30 or 34 | 120-277 | 0-10    | 840     | 3100, 3750 or 4250 | 125 | ≥50,000  | E      |
| 61689       | <u>VOLUME5AS/034UNVD850/24U/WH/E</u> | 25, 30 or 34 | 120-277 | 0-10    | 850     | 3100, 3750 or 4250 | 125 | ≥50,000  | E      |
| 61690       | <u>VOLUME5AS/045UNVD835/24U/WH/E</u> | 34, 38 or 45 | 120-277 | 0-10    | 835     | 4250, 4750 or 5600 | 125 | ≥50,000  | E      |
| 61691       | <u>VOLUME5AS/045UNVD840/24U/WH/E</u> | 34, 38 or 45 | 120-277 | 0-10    | 840     | 4250, 4750 or 5600 | 125 | ≥50,000  | E      |
| 61692       | <u>VOLUME5AS/045UNVD850/24U/WH/E</u> | 34, 38 or 45 | 120-277 | 0-10    | 850     | 4250, 4750 or 5600 | 125 | ≥50,000  | E      |
| 61693       | <u>VOLUME5AS/030UNVD835/14U/WH/E</u> | 20, 25 or 30 | 120-277 | 0-10    | 835     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61694       | <u>VOLUME5AS/030UNVD840/14U/WH/E</u> | 20, 25 or 30 | 120-277 | 0-10    | 840     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |
| 61695       | <u>VOLUME5AS/030UNVD850/14U/WH/E</u> | 20, 25 or 30 | 120-277 | 0-10    | 850     | 2500, 3125 or 3750 | 125 | ≥50,000  | E      |

## ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer Family Overview

---



- Both the UltraLED Retrofit Doorkits and Volumetric Troffers will continue to be offered.
- These families continue to offer 347-480V as well as controls options with ENLIGHTED, LUTRON, AND ENCELUM.





# ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer

## Nomenclature Review

### Ordering Guide

| RDORKIT          | 5A            | S                | / XX                | UNX      | D         | 8       | XX         | / XX        | U             | / WH         | –                             |
|------------------|---------------|------------------|---------------------|----------|-----------|---------|------------|-------------|---------------|--------------|-------------------------------|
| Product Name     | Generation    | Lumen Selectable | Wattage             | Voltage  | Dimming   | CRI     | Color Temp | Size        | Mounting      | Color/Finish | Options                       |
| RDORKIT =        | 5A =          | S =              | 30 = 20, 25, or 30W | UNV =    | D = 0-10V | 8 = >80 | 35 = 3500K | 14 = 1x4 ft | U = Universal | WH = White   | Blank = no option             |
| Retrofit Doorkit | Generation 5A | Lumen Selectable | 34 = 25, 30, or 34W | 120-277V |           |         | 40 = 4000K | 22 = 2x2 ft | Mounting      |              | E = Emergency Battery Back-up |
|                  |               |                  | 45 = 34, 38, or 45W |          |           |         | 50 = 5000K | 24 = 2x4 ft |               |              |                               |

### Ordering Guide

| VOLUME             | 5A            | S                | / XX                | UNX      | D         | 8       | XX         | / XX        | U             | / WH         | –                             |
|--------------------|---------------|------------------|---------------------|----------|-----------|---------|------------|-------------|---------------|--------------|-------------------------------|
| Product Name       | Generation    | Lumen Selectable | Wattage             | Voltage  | Dimming   | CRI     | Color Temp | Size        | Mounting      | Color/Finish | Options                       |
| VOLUME =           | 5A =          | S =              | 30 = 20, 25, or 30W | UNV =    | D = 0-10V | 8 = >80 | 35 = 3500K | 14 = 1x4 ft | U = Universal | WH = White   | Blank = no option             |
| Volumetric Troffer | Generation 5A | Lumen Selectable | 34 = 25, 30, or 34W | 120-277V |           |         | 40 = 4000K | 22 = 2x2 ft | Mounting      |              | E = Emergency Battery Back-up |
|                    |               |                  | 45 = 34, 38, or 45W |          |           |         | 50 = 5000K | 24 = 2x4 ft |               |              |                               |



## ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer

### Key Takeaways

---

- Application : The ValueLED Retrofit Doorkit and Volumetric Troffer are offered in three sizes (1'x4', 2'x2', and 2'x4'). The addition of the 1'x4' options fills an existing gap in our current portfolio
- All models are DLC Premium listed to maximize rebate opportunities
- The lumen selectability feature allows for a wide range of lumen output options with fewer NAEDs, reducing the complexity of inventory management

---

# THANK YOU