



Product Number: 54307

Order Abbreviation: 35MR16/SP10/C(FRB)12V

General Description: Tungsten Halogen Tru-Aim MR16 STANDARD Axial Filament UV-Filter Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base 35Watt 12Volt Spot Beam

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	35MR16SP10CFRB 12V 20/CS 1/SKU
ANSI Code	FRB
Average Rated Life (hr)	2000
Base	GU5.3 Bipin
Beam Angle (deg)	10
Beam Type	SP
Bulb	MR16
Centerbeam Candlepower (cp)	6000
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2900
Diameter (in)	2.008
Diameter (mm)	51.00
Ecologic	YES
Family Brand Name	TRU-AIM Standard
Filament	AXIAL
Horizontal Beam Angle (deg)	10
Lamp Finish	Covered
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45.0
Nominal Voltage (V)	12.00
Nominal Wattage (W)	35.00
Vertical Beam Angle (deg)	10



Footnotes

- UV Filter capsul with axial filament in covered dichroic reflector.
- Max. seal temperature 370 C (662F)
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

