STELANIN	Product Number:	23503
	Order Abbreviation	F96T12CWXSSUPC
	General Description:	60W, 96 inch MOL, T12 instant start Slimline SUPER SAVER fluorescent lamp, Cool White Deluxe phosphor, 4100K color temperature, 87 CRI, UPC code. VIVID Color: High CRI lamps for color critical applications.

* Full Case Required

Abbrev. With Packaging Info.	F96T12CWXSSUPC 15/CS 1/SKU
Actual Length (in)	94.000
Actual Length (mm)	2387.60
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	87
Color Temperature/CCT (K)	4100
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	SuperSaver®
Family Brand Name Industry Standards	SuperSaver® ANSI C78.81 - 2001
2	-
Industry Standards	ANSI C78.81 - 2001
Industry Standards Initial Lumens at 25C	ANSI C78.81 - 2001 3850
Industry Standards Initial Lumens at 25C Mean Lumens at 25C	ANSI C78.81 - 2001 3850 3390
Industry Standards Initial Lumens at 25C Mean Lumens at 25C Nominal Length (in)	ANSI C78.81 - 2001 3850 3390 96.000
Industry Standards Initial Lumens at 25C Mean Lumens at 25C Nominal Length (in) Nominal Length (mm)	ANSI C78.81 - 2001 3850 3390 96.000 2438.40
Industry Standards Initial Lumens at 25C Mean Lumens at 25C Nominal Length (in) Nominal Length (mm) Nominal Wattage (W)	ANSI C78.81 - 2001 3850 3390 96.000 2438.40 60.00
Industry Standards Initial Lumens at 25C Mean Lumens at 25C Nominal Length (in) Nominal Length (mm) Nominal Wattage (W) Outside Diameter (in)	ANSI C78.81 - 2001 3850 3390 96.000 2438.40 60.00 1593

Product Information



Footnotes

- Approximate initial lumens after 100 hours operation. ٠
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI • specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer. •