



**Product  
Number:**

49385

**Order  
Abbreviation:**

QHE 3x32T8/UNV ISN-SC-1-CC-B

**General  
Description:**

QHE3X32T8UNVISNSC1CCB10/CS 1/SKU

#### Product Information

Abbrev. With Packaging Info.	QHE3x32T8UNVISNSC1CCB 10/CS 1/SKU
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Family Brand Name	QUICKTRONIC Professional High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V



**QUICK 60+**  
25271PK N.C. K.C. H.T.

#### Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Lampholder must be shorted per diagram
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Complies with UL935 requirements for "Type CC" rating
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Minimum starting temperature: -20 F / -29 C
- Insulate unused leads individually for 600V
- CSA certified.
- ANSI C82.11 where applicable.
- NO PCB (Polychlorinated Biphenyl)
- Remote mounting up to 20 feet
- Lamp Striation Control (LSC) may minimize or eliminate lamp striations which can occur in T8 energy savings lamps.