




Product Number: 49879

Order Abbreviation: QHE 2x59T8/UNV ISH

General Description: 2-lamp 59wT8 (8') High Efficiency Instant Start electronic ballast, universal voltage, high ballast factor, 10-pk.

Product Information

Abbrev. With Packaging Info.	QHE2x59T8UNVISH 10/CS 1/SKU
Ballast Factor	1.15
Ballast Height H (in)	1.5350
Ballast Length L (in)	8.2890
Ballast Width W (in)	2.3900
Circuit Type	Parallel
Family Brand Name	QUICKTRONIC High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	840V
Power Factor	>0.98
Primary Lamp Type	FO96T8 XP (59W)
Sound Rating	A
Starting Method	Instant Start
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Max Case Temperature	70°C



Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps

- Cutout Lampholder
- CSA certified.
- ANSI C82.11 where applicable.
- NO PCB (Polychlorinated Biphenyl)
- Remote mounting up to 20 feet