

UPC Code: 07847736193 Country Of Origin: Mexico

3033-2

Brand Features

Leviton's Industrial Grade AC toggle switches for extra heavy-duty applications represent top-of-the-line quality and peak performance. Leviton uses the finest materials available and the highest production standards to produce industrial switches of unmatched versatility and reliability.

Item Description

30 Amp, 120/277 Volt, Toggle 3-Way AC Quiet Switch, Extra Heavy Duty Spec Grade, Self Grounding, Back &Side Wired - BROWN

Technical Information

AC Horsepower Ratings HP Rating: 2HP-120V 2HP-240V-277V Max. Amperage: 24 Amp

Electrical Specifications

Amperage: 30 A

Voltage: 120/277 VAC Grounding: Self-Grounding Dielectric Voltage: Withstands 1500V for 1 minute Overload UL20 Test: 100 cycles of OL at 4.8 times rated current Temperature Rise: Maximum 30

degress C rise Endurance: 50,000 cycles minimum

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 65°C

Material Specifications

Strap Material: Steel Base Material: Thermoplastic Toggle: Polycarbonate Cover Material: Thermoplastic Contact Material: Silver Alloy Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Ground Clips: Brass Color: Brown Mechanical Specifications Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd

Terminal Accom.: 14-#10 AWG back wired; #14-#12 AWG side wired

Product ID: Ratings are permanently marked on device

Torque Range: 12-14 inch pounds **Termination:** Back or Side Wire


Product Features

Color: Brown Grounding: Self-Grounding Voltage: 120/277 VAC HP Rating: 2HP-120V 2HP-240V-277V Body Material: Thermoplastic Strap Material: Steel Function: 3-Way Grade: Extra Heavy-Duty Industrial Specification Grade Device Type: Toggle Switch

Standards and Certifications


NEMA: WD-1 & WD-6 ANSI: C-73 UL Fed Spec WS896E: File #E7458 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 RoHS: Compliant Warranty: 10 Year Limited







Wiring Diagram 3-Way to 3-Way



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

