





UPC Code: 07847713033



# 5351

#### **Brand Features**

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

### Item Description

Single Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp. 125 Volt. Side Wire.NEMA 5-20R. 2-Pole. 3-Wire. Self-Grounding - Brown

#### **Technical Information**

**AC Horsepower Ratings** At Rated Voltage: 1 HP **Electrical Specifications** 

**Grounding:** Self-Grounding

Amperage: 20 A Voltage: 125 VAC

Pole: 2 Wire: 3

Dielectric Voltage: Withstands 2000V

per UL498

**Current Limiting:** Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

**Environmental Specifications** Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications

Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon Terminal Screws: Plated Brass **Grounding Screw: Plated Steel** 

**Ground Clips: Brass** 

Line Contacts: Phosphor Bronze Strap Material: Galvanized Steel with

**Riveted Ground Contacts** Clamp Nuts: Zinc-Plated Steel

Color: Black

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 14-10 AWG **Product ID:** Ratings are permanently

marked on device

Torque Range: 14-16 inch pounds

Termination: Side Wire

**Product Features** 

**Grounding: Self-Grounding** 

**NEMA: 5-20R** 

Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon

Color: Black

Device Type: Single Receptacle Outlet

Feature 4: Smooth Face Grade: Heavy-Duty Industrial

Specification Grade

Standards and Certifications

NEMA: WD-6 **ANSI:** C-73


UL498: File E13399

UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105


**NOM: 057** 

Warranty: 10 Year Limited

# **Dimensional Diagram**



# Wiring Diagram



6-20R

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

