



# Representative image shown.

UPC Code: 07847797405
Country Of Origin: Mexico

# L7939

3 Inch, 45-Degree, Male, Malleable Iron Body, Liquid-Tight Metal Core Conduit, Strain-Relief Grip

Liquid-Tight Grips are woven stainless steel mesh with an anodized aluminum body for corrosion-resistance. They are used to connect liquid-tight flexible metal conduit to electrical enclosures to prevent conduit pullout. Each fitting is supplied with an insulated throat to ensure conductor insulation and protect against damage caused by flexing, heat expansion or contraction. Liquid-Tight Grips are recommended in the wiring of motors and any electrical enclosure where liquid-tight conduit is subject to motion or strain.

#### **Technical Information**

Material Specifications

Body Material: Malleable Iron Grip Material: Stainless Steel Color / Feature: Insulated

**Mechanical Specifications** 

Fitting Type: Liquid-Tight Metal Core

NPT Size: 3

Fitting Style: 45-Degree Fitting Gender: Male Weave: Double Mesh Length: 10-5/8 Standards and Certifications

Standards and Certifications: UL/CSA

Warranty: 2-Year Limited

**Product Features** 

Device Type: Strain Relief Grip

### SPECIFICATION SUBMITTAL

	JOB NAME:	CATALOG NUMBERS:
I		
I	JOB NUMBER:	

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920  $\cdot$  FAX: +1-800-832-9538  $\cdot$  Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

# Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

