

M5362-SCB





UPC Code: 07847774018
Country Of Origin: Mexico

*Eligible for ARRA funded projects > \$7,443,000

NEMA: 5-20R





M5362-SCB

Brand Features

The Lev-Lok® Modular Wiring Device System is engineered for fast and easy installation. These devices employ a simple twist and lock wiring module that ensures a safe, reliable connection while at the same time providing for extremely fast and easy installation. Lev-Lok brand wiring devices address the reliability and performance concerns of specification engineers without sacrificing the contractor's need for fast, easy installation.

Item Description

<meta http-equiv="Content-Type" content="text/html; charset=UTF-8"><meta httpequiv="Content-Style-Type" content="text/css"><meta name="Generator" content="Cocoa HTML Writer"><meta name="CocoaVersion" content="1348.17"> <style type="text/css">>p.p1 {margin: 0.0px 0.0px 0.0px 0.0px; font: 14.0px Helvetica; color: #4444444; -webkit-text-stroke: #444444} span.s1 {font-kerning: none}

</style>

<20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Lev-Lok® Duplex Receptacle, Straight Blade, Fed Spec, Heavy Duty Industrial Specification Grade, Self-Grounding, Modular Terminals, Steel Strap -- BLUE <meta http-equiv="Content-Type" content="text/html; charset=UTF-8"><meta http-equiv="Content-Style-Type" content="text/css"><meta name="Generator" content="Cocoa HTML Writer"><meta name="CocoaVersion" content="1348.17"><<style type="text/css">>p.p1 {margin: 0.0px 0.0px 0.0px 0.0px; font: 12.0px 'Helvetica Neue'; -webkit-text-stroke: #000000} span.s1 {font-kerning: none}

</style>

Mating Lev-Lok Wiring Module Required for Use

Technical Information

AC Horsepower Ratings

Horsepower Rating: 1 HP

Electrical Specifications

Dielectric Voltage: Withstands 2000V

per UL498

Grounding: Self-Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Current Interrupting: Certified for current interrupting at full rated current

Voltage: 125 Volt Amperage: 20 Amp

Wire: 3 Pole: 2

Environmental Specifications

Operating Temperature: -40 °C to 60

°Ċ

Flammability: Rated V-2 per UL94

Material Specifications

Mounting Strap: Galvanized Steel

Ground Clips: Brass

Mounting Screws: Triple Combination

Head, Steel

Cover Material: Nylon

Line Contacts: 0.040" Thick Solid Brass

Locking Pins: Solid Brass Bushing: Solid Brass Base Material: Nylon

Mechanical Specifications

Product ID: Ratings are permanently

marked on device

Termination: Modular Terminals, #10 -

#14 AWG for controlled "hot"

Product Features

Controlled Outlets:

Color: Blue


Device Type: Duplex Receptacle

NEMA: 5-20R

Standards and Certifications
Warranty: 10 Year Limited
CSA C22.2 No. 42: File 152105
UL Fed Spec WC-596: File E13399

ANSI: C-73 **NOM:** 057

UL498: File E13399 **NEMA:** WD-1 & WD-6



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

