





Color :  Gray

UPC Code : 078477841235

Country Of Origin : China



Available Colors :



T5633-GY

5.1A USB Type A/Type-C Wall Outlet Charger with 15A Tamper-Resistant Outlet

15 Amp, 125 Volt, Decora Tamper-Resistant Outlet. NEMA 5-15R, 25+W (5.1 Amp), Type A and Type-C USB In Wall Charger, Grounding, Side Wired & Back Wired - Gray

- **SMART** – Built-in smart chip recognizes the individual device's charging requirements to optimize the charge (Does not provide Power Delivery. See Leviton [T5635](#))
- **POWERFUL** - Two high-powered charging ports deliver a combined total of 5.1A charging current and 25+ watts of power
- **CONVENIENT** – No more searching for charging adapters! Upgrade so you can charge electronics leaving the outlets free for additional power needs
- **THE FUTURE OF CHARGING** – USB Type-C provides faster charging and is emerging as the standard port on many phones, tablets and laptops
- **ENHANCED SAFETY** – Built-in overcurrent protection helps protect electronics from receiving too much power, which can damage the device

Technical Information

Product Features

Amperage : 15 A

Brand : Decora

Color : Gray

Grade : Commercial Specification Grade

Grounding : Grounding

Horsepower Rating : 15A-1/2 HP

NEMA : 5-15R

Product Type : Outlet/USB Combo

Ratings : 15A-125V

Type : Type A/C Duplex Receptacle

Voltage : 125 VAC

Wallplate : Not Included

Standards and Certifications

FCC Part 15 : Class B

Flammability : Rated V-0 per UL 94

Listed : cCSAus

NOM : 057

Operating Temperature : -10°C to 40°C

UL 1310 : Yes

UL 498 : Yes

Warranty : 5-Year Limited

Electrical Specifications

Amperage : 15 A

Body Material : Thermoplastic

Color : Gray

Cover Material : Thermoplastic

Grounding : Grounding

Horsepower Rating : 15A-1/2 HP

Ratings : 15A-125V

Strap Material : Steel

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -10°C to 40°C

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Back & Side

Torque Range : 12-14 inch pounds

Material Specifications

Body Material : Thermoplastic

Color : Gray

Cover Material : Thermoplastic

Grade : Commercial Specification Grade

Strap Material : Steel

Mechanical Specifications

Listed : cCSAus

NOM : 057

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Back & Side

Torque Range : 12-14 inch pounds

Warranty : 5-Year Limited

Features and Benefits

- Ideal for residential and commercial applications including kitchens, bedrooms, home offices, college dormitories, airport lounges, hospitals, salons and spas, hotels, meeting rooms, cafes, restaurants and more
- Smart chip technology recognizes and optimizes the charging requirements of individual devices including Apple, Samsung, Nexus, Pixel and more
- The Type-C Port provides up to 59% faster charging power versus competitors*
- One Type A Port and one Type-C Port; combined total of 5.1A of charging power
 - Type-C Port can charge maximum 3 Amps @ 5V
 - Type A Port can charge maximum 2.4 Amps @ 5V
- Tamper-Resistant improves child safety – built-in shutter prevents access by most non-rated/foreign objects
- USB Ports tested to withstand over 10,000 insertions
- Charges most Type A and Type-C USB powered devices
- Type-C Port permits the cables to be inserted easily in either direction
- Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates
- Compatible with USB 3.0, 2.0, 1.1 devices
- No data transfer capability
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates.

Wallplate sold separately

* Testing performed using Lightning cable on C Port with iPhone 7, iPad Mini 1, iPad Pro 9.7

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

