



3880-DIN

15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, DIN-Rail Mountable Modules Receptacle, Straight Blade, Industrial Grade, Grounding, Surge Duplex, Indicator Light & Audible Alarm, Terminal Block Wired, Strap - BLUE

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Color:  Blue

UPC Code: 07847707622

Country Of Origin: Mexico

NEMA:
5-15R



Technical Information

Electrical Specifications

Amperage: 15 A

Current Limiting: Full Rated Current

Dielectric Voltage Withstand: 2000V minimum per UL 498

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Environmental Specifications

Flammability: UL94V-2

Operating Temperature: -10°C to 60°C

Storage Temperature: -20°C to 85°C

Material Specifications

Body Material: Thermoplastic

Face Material: Thermoplastic Nylon

Line Contacts: Nickel-Plated Brass

Mechanical Specifications

Terminal Accom.: 12-18 AWG

Performance Data

Diagnostics: Indicator Light & Audible Alarm

Joules Rating: 560

Maximum Surge Current, Per Mode (Per Phase): 9kA (18kA)

MCOV: 150V

Noise Rejection: -35 dB at 5kHz-5MHz

Nominal Discharge Current Rating: 3kA

Protection Mode: 3 Mode

VPR: L-N:500V, L-G:600V, N-G:600V

Product Features

Body Material: Thermoplastic

Color: Blue

Face Material: Thermoplastic Nylon

NEMA: 5-15R

Noise Rejection: -35 dB at 5kHz-5MHz

Voltage: 125 VAC

Standards and Certifications

Agency Certifications: UL 498, UL 1449 3rd Edition Recognized Component

ANSI: C-73

NEMA: WD-6

NOM: 057

Warranty

Product Warranty: 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

