

DuraPort® Industrial Patch Cords

APPLICATION

DuraPort industrial products provide IP67-class protection to safeguard your connectivity from humidity/moisture, corrosive materials, temperature extremes, and other conditions often found in the industrial environment.



SPECIFICATION

Industrial Plug-to-Industrial Plug and Industrial Plug-to-RJ-45 Plug patch cords shall be IP67 rated. The patch cords shall be stranded tinned UTP, with an 8-position modular plug on each end. The cords shall be available in lengths of 3, 5, 7, 10, 15, 20, and 50 feet. The cords shall be compliant with ANSI/TIA-1005 and ANSI/TIA-568. All plastics used in construction of the connector bodies shall be fire retardant with a UL flammability rating of 94V-0.

WARRANTY INFORMATION

For a copy of Leviton product warranties, visit www.leviton.com/warranty.

COUNTRY OF ORIGIN

Taiwan

FEATURES

- IP67-rated Environmental Sealing (dust/water protection)
- Industrial Plug o-ring and gasket provides dual seal feature
- Withstands chemical wash down requirements for disinfection and sterilization in health care facilities, as established by the CDC
- Sealing nut provides strain relief and seal to prevent contamination from liquids and dust
- Patch cords available in Industrial Plug-to-Industrial Plug and Industrial Plug-to-RJ-45 Plug
- Available in seven standard lengths (custom lengths available)
- Twist-lock design for faster installation and changes
- Encapsulated RJ-45 design protects integral components
- Patented design
- Cat 6 UTP cable

DESIGN CONSIDERATIONS

- ANSI/TIA channel performance limits the total length of work area and equipment room cords to 32 feet (ten meters) per
- ANSI/TIA-568-C or 88.6 feet (27 meters) in a MUTOA application
- Designed for use with DuraPort Industrial Connector Housings to provide IP67 protection against dust and water

STANDARDS COMPLIANCE

Complies with ANSI/TIA-1005 and ANSI/TIA-568. cULus Listed (UL 1863, CAN/CSA-C22.2 No. 182.4-1990).

PHYSICAL SPECIFICATIONS


Ingress Protection:	IP67 (dust/water)
Corrosion:	Resistant to most common chemicals, oils, and cleaning agents
Temperature:	-40° C to 65° C (-40° F to 149° F)
Vibration:	Frequency Range 10-500HZ Acceleration 5g (operational) Mating Cycles: 750 minimum
Materials:	
Plug Housing	Polybutylene terephthalate (PBT), UL 94V-0
Cable Outer Jacket	Thermoplastic Elastomer
Gasket and O-Ring	Thermoplastic Elastomer
Connector Boot	Thermoplastic Elastomer

ELECTRONIC FILES

For CAD files, typical specs, or technical drawings (.DXF, .DWG), visit www.leviton.com.

D6720-xxE, D6721-xxE

The DuraPort® System



D6720-xxE, D6721-xxE

DURAPORT INDUSTRIAL PATCH CORDS

Description	Part No.
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 3 feet	D6720-03E
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 5 feet	D6720-05E
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 7 feet	D6720-07E
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 10 feet	D6720-10E
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 15 feet	D6720-15E
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 20 feet	D6720-20E
DuraPort Industrial Plug-to-Industrial Plug Patch Cords, 50 feet	D6720-50E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 3 feet	D6721-03E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 5 feet	D6721-05E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 7 feet	D6721-07E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 10 feet	D6721-10E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 15 feet	D6721-15E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 20 feet	D6721-20E
DuraPort Industrial Plug-to-RJ-45 Plug Patch Cords, 50 feet	D6721-50E



Leviton Network Solutions
 2222 - 222nd St. SE
 Bothell, WA 98021-4416

Asia / Pacific
 T +1.631.812.6228
 E infoasean@leviton.com

Canada
 T +1.514.954.1840
 E pcservice@leviton.com

Caribbean
 T +1.954.593.1896
 E infocaribbean@leviton.com

China
 T +852.2774.9876
 E infochina@leviton.com

Colombia
 T +57.1.743.6045
 E infocolombia@leviton.com

tel 1-800-824-3005
 tel +1-425-486-2222
 appeng@leviton.com
 www.leviton.com

Europe
 T +44.0.1592.772124
 E customerservice@brand-rex.com

India / SAARC
 T +971.4.886.4722
 E infoindia@leviton.com

Mexico
 T +52.55.5082.1040
 E lsamarketing@leviton.com

Middle East & Africa
 T +971.4.886.4722
 E lmeinfo@leviton.com

South Korea
 T +82.2.3273.9963
 E infokorea@leviton.com