



**UPC Code :** 078477188354

**Country Of Origin :** Please Contact Customer Service.

## OSWLR-I0W

Long Range, PIR, Occupancy Sensor lighting control, Wall Mounted, 24VDC, 15mA power consumption, 10' mounting height, 100' length x 30' width (major motion only), Red LED=PIR, auto adapting, walk-through, time delay 30s-30m, test mode (6s time delay for 15m with auto exit), connect gray wire for photocell ambient light hold-off, 360 degree harmonic wheel (rotatable), mounting height 8'-10', Patented Canopy Knuckle for versatile wall and ceiling mounting options, cUL/NOM/ANCE listed, Color: off-white.

Specifically designed for long, relatively narrow spaces such as hallways and corridors, the OSWLR-I occupancy sensor provides long range and high sensitivity. The OSWLR-I occupancy sensor is a "long range" lens. This lens provides coverage up to 100 ft. When mounted 10 ft. Above the floor. Can be mounted lower if needed. The mounting base, provided with the sensor, allows quick and easy mounting in corners, on walls or on ceilings. The most common applications are factory storage areas, warehouse aisles and corridors. The OSWLR-I Sensor combines PIR technology with a microprocessor based digital architecture. By eliminating false triggering, the sensor provides a trouble-free "install and forget" solution for lighting control.

### Technical Information

#### Product Features

**Adjustment :** Self-Adjusting  
**Code Compliance :** California Title 24  
**Color :** White  
**Coverage (Sq.Ft.) :** 100FT x 14FT @ 10FT Height  
**Current Consumption :** 15mA  
**Housing Material :** High-Impact, Injection Moulded Plastic  
**Input Voltage :** 24VDC  
**LED Disable :** LEDS Enable/LEDS Disable  
**Load Rating :** Uses Power Pack  
**Made in USA :** No  
**Manual Time Adjustment :** 30s-30m, 6s Test Mode  
**Pattern Degrees :** 08  
**Photo Cell :** Ambient Override ON  
**Photo Cell Adjustment :** 20 to 3000 Lux  
**Photocell Factory Preset :** 3000 Lux (disable photocell)  
**Product Line :** OSWLR  
**Sensitivity Adjustment :** 0 to 100 Pct  
**Sensitivity Factory Preset :** Infrared 75 Pct  
**Sensor Technology :** Passive Infrared  
**Sensor Type :** Wall Mount  
**Standards and Certifications :** CUL/US Cert  
**Technology :** Passive Infrared  
**Timer Factory Preset :** 10 Minutes  
**True White :** No  
**Warranty :** 5-Year Limited

#### Electrical Specifications

**Current Consumption :** 15mA

**Input Voltage :** 24VDC

**Line Voltage :** No

**Load Rating :** Uses Power Pack

**Output Voltage :** 24VDC w/Short Circuit Protection

**Voltage :** 24 VDC

#### Standards and Certifications

**ANCE :** Compliant  
**ASHRAE :** Standard 90.1 Compliant  
**CUL/US :** Listed 9034  
**Code Compliance :** California Title 24  
**FCC :** Compliant  
**NAFTA Compliant :** No  
**NOM :** 057  
**Operating Humidity :** 0 Pct to 95 Pct Relative, Non-Condensing  
**Operating Temperature :** 32F to 104F 0C to 40C

#### Mechanical Specifications

**Color :** White  
**Coverage (Sq.Ft.) :** 100FT x 14FT @ 10FT Height  
**Housing Material :** High-Impact, Injection Moulded Plastic  
**Isolated Relay :** No  
**LED Indicator :** Red Infrared Motion  
**Major Motion Area :** 100X14 Feet  
**PIR Lens Type :** Multi-Element Long Range  
**Pattern Degrees :** 08  
**Photo Cell :** Ambient Override ON  
**Sensor Technology :** Passive Infrared  
**Sensor Weight :** 6oz/171g  
**Wire Leads :** Color Coded 6 Inch

### Features and Benefits

- Combines PIR Technology with a microprocessor based digital architecture. By eliminating false triggering, the sensor provides a trouble-free "install and forget" solution for lighting control
- Self-adjusting settings continuously analyze and adjust infrared sensitivity, timer operation, and long term performance
- Adjustable swivel neck rotates 80 degrees vertically and 60 degrees horizontally. Can be used for ceiling or wall mounting
- Ambient light override prevents lights from turning on when there is ample natural light
- Self-Adjusting delayed-off time interval settings for 30 seconds to 30 minutes. Compensates for real-time occupancy patterns- preventing unnecessary on/off switching
- Non-volatile memory preserves all automatic and manual settings during power outages.
- Fast, simple installation using 3 color-coded low-voltage wires and a single mounting post
- Excellent 5-Year Limited warranty
- Typical Applications: Long narrow spaces such as Warehouse Aisles, Hallways and Corridors where a low mounting height is desirable


#### Patents\*

US7211798

USD548125

USD511705

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



#### SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

