





UPC Code: 07847750928 Country Of Origin: Mexico

NEMA: 5-20R



5362-IGE

Item Description

Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Black

Technical Information

AC Horsepower Ratings At Rated Voltage: 1 HP

Electrical Specifications Grounding: Self-Grounding

Amperage: 20 A Voltage: 125 VAC

Pole: 2 Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications Face Material: Nylon Body Material: Nylon

Line Contacts: Phosphor Bronze Terminal Screws: Plated Brass Grounding Screw: Brass 8-32 Strap Material: Galvanized Steel Clamp Nuts: Galvanized Steel Isolated Ground System: Brass

Color: Black

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 14-10 AWG Product ID: Ratings are permanently

marked on device

Torque Range: 14-16 inch pounds Termination: Back or Side Wire

Product Features NEMA: 5-20R Color: Black

Device Type: Duplex Receptacle Outlet

Feature 4: Smooth Face Grade: Heavy-Duty Industrial Specification Grade

Standards and Certifications


NEMA: WD-6 **ANSI:** C-73

UL498: File E13399

UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105

NOM: 057

Warranty: 10 Year Limited



Drawing Applies to 15 & 20A Devices

SPECIFICATION SUBMITTAL

	JOB NAME:	CATALOG NUMBERS:
ı		
ı	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

