



CNL103

CNL-1000 Hi-Capacity No Lead Frost Proof Yard Hydrant

Submittal Data



CNL103



BVBADNL75

Job or Customer _____

Engineer _____

Contractor _____

Submitted by _____ Date _____

Approved by _____ Date _____

Purchase Order Number: _____

Date Required: _____

Cut Away View - Shows the plunger inside the valve body

Technical Data - Hydrant

CNL103 - Hi-Capacity CNL-1000 No Lead Frost Proof Yard Hydrant

Inlet - 1" NPT in No Lead Brass Casting

Outlet - 3/4" Hose Thread

Stainless Steel Operating Rod Thru Teflon Packing

Brass and Molded Rubber Plunger

1" No Lead Galvanized Stand Pipe

Bury Depth - 3'

Technical Data - Vacuum Breaker

BVBADNL75 - No Lead Brass Vacuum Breaker

3/4" Hose

No Lead Brass Finish

Automatic Drain

ASSE-IAPMO Code approved and marked

CNL-1000 Hi-Capacity Flow Rates

WATER SYSTEM PRESSURE	GALLONS PER MINUTE (GPM)										
	0	5	10	15	20	25	30	35	40	45	50
10 PSI	12 GPM @ 10 PSI										
20 PSI	18 GPM @ 20 PSI										
30 PSI	24 GPM @ 30 PSI										
40 PSI	30 GPM @ 40 PSI										
60 PSI	38 GPM @ 60 PSI										
80 PSI	45 GPM @ 80 PSI										
100 PSI	51 GPM @ 100 PSI										

NOTE: Most common 1/2 hp submersible pumps output is 10GPM.



315 Flindt Drive
P.O. Box 392
Storm Lake, Iowa
50588-0392 U.S.A.

Main # (712) 732-2760
U.S. & Canada # (800) 831-6962

Fax # (712) 732-4401
U.S. Fax # (800) ANY FLOW
www.merrillmfg.com