



Vinyl Insulated Reducing Butt Splice Connector



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F(75°C) 600 Volts


INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Copper Brazed Seam

Dimensions = Inches

Cat. No.	Wire Range AWG	Color Code	L	D	d1	D2	Bag Qty	Master Bag Qty
12135	16-14 To 22-18	Blue with Red Ring	.965	.177	.067	.091	100	1000
12136	12-10 To 22-18	Yellow with Red Ring	1.22	.248	.067	.134	100	1000
12137	12-10 To 16-14	Yellow with Blue Ring	1.22	.248	.091	.134	100	1000
12138	8 To 16-14	Red with Blue Ring	1.406	.335	.091	.177	100	1000
12139	8 To 12-10	Red with Yellow Ring	1.406	.335	.134	.177	100	-
12140	6 To #8	Blue with Red Ring	1.172	.413	.177	.232	100	-

Nylon Insulated Butt Splice Connectors



MAXIMUM ELECTRIC CURRENT:

Awg	26	24	22	20	18	16	14	12	10
Amp	5.5	7	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

CONNECTOR MATERIAL: Copper


INSULATION MATERIAL: Nylon

FEATURES: Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	L	D	d1	Material	Bag Qty	Master Bag Qty
12142	Yellow	26-22	.787	.079	.051	Tubular Copper	100	1000
12144	Red	22-16	1.075	.126	.067	Copper Plate	100	1000
12146	Blue	16-14	1.075	.150	.091	Copper Plate	100	1000
12148	Yellow	12-10	1.075	.209	.134	Copper Plate	100	1000
12149	Red	8	1.457	.272	.181	Copper Plate	100	-

Nylon Insulated Butt Splice Connector Flared Entry



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Tubular Copper

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	L	D	d1	Bag Qty	Master Bag Qty
12192	Red	22-16	.992	.157	.067	100	1000
12193	Blue	16-14	.992	.177	.091	100	1000
12194	Yellow	12-10	1.11	.248	.134	100	1000