

## Electrical Mast Roof Flashing



- ▶ Flexible EPDM Rubber Base with Flexible Soft Aluminum Strip designed to seal to most panel configurations and roof pitches regardless of pipe location
- ▶ Resists Ozone and UV Light
- ▶ One Piece Construction for Fast Installation
- ▶ -67°F to +212°F
- ▶ IAMPO Cert. No. 3121 Approved for use with Type B Vents
- ▶ For use for Shingle Roof Applications
- ▶ Not for hot mopped or built up roofs
- ▶ Cannot use Petroleum based products or paint on flashing collar or plastic

Cat. No.	Outside Diameter of Pipe to be Flashing	Base		Case Qty	Wt/ Case
		Length	Width		
G14090	1/4" to 5-3/8"	15"	15"	4	2

## SIDELASH Thermoplastic Self-Seal Wall Flashings



- ▶ Designed to seal around piping penetrations through outside walls
- ▶ Slips easily over vent pipe - self-sealing to vent pipe surface
- ▶ Self-sealing elastomeric collar attached to a durable flexible hard plastic base
- ▶ Collar will not crack, chip, peel or separate from base
- ▶ Eliminates caulking - prevents moisture intrusion - no sealing compound required
- ▶ Absolutely leak-proof & fits most wall constructions
- ▶ Seals against air penetration - reduces energy costs
- ▶ Prevents bug or vermin intrusion
- ▶ Accommodates all vent types - ie: plastic, copper, steel or cast iron

Cat. No.	Outside Diameter of Pipe to be Flashing	Base		Case Qty	Wt/ Case
		Length	Width		
G12805	1/2" to 2-1/2"	8"	8.5"	12	4
G12806	3" to 6"	12"	12.5"	12	7

## Thermoplastic Base Self Seal Roof Flashings



- ▶ Self-sealing elastomeric collar attached to a sturdy rigid thermoplastic base
- ▶ No caulking needed
- ▶ Absolutely leak proof
- ▶ Slips easily over pipe vent
- ▶ Self-sealing to vent pipe surface
- ▶ Self-adjusting to roof pitches up to 45°
- ▶ Base will not crack or warp
- ▶ Accommodates all vent pipe types - ie: plastic, copper, steel, cast iron
- ▶ Use in Shingled Roof Applications
- ▶ Not for hot mopped or built up roofs

Cat. No.	Outside Diameter of Pipe to be Flashing	Base		Case Qty	Wt/ Case
		Length	Width		
G14101	1-1/4" to 1-1/2"	12-7/8"	9-1/4"	12	6
G14102	2" to 2-1/2"	12-7/8"	9-1/4"	12	6
G14103	3"	15"	11-1/4"	12	8
G14104	4"	16"	12"	12	9

## Rubber Flexible Roof Flashings



- ▶ Roof Flashing slides over vent pipe - accommodates pitch up to 40°
- ▶ Commercial or Residential Applications
- ▶ Rubber sealing collar seizes the vent pipe with a locking grip preventing leakage Accommodates all vent types - ie: plastic, copper, steel or cast iron
- ▶ One piece construction molded from military grade elastomer assures long life & all weather protection - will not crack, chip or peel; oil, ozone & UV resistant
- ▶ Flexible base conforms to wide range of roof pitches, contours & surfaces
- ▶ For use in Shingled Roof or Clay Tile Applications
- ▶ Not for use in hot mopped or built up roofs

Cat. No.	Outside Diameter of Pipe to be Flashing	Base		Case Qty	Wt/ Case
		Length	Width		
G30101	1-1/4" to 1-1/2"	11-1/4"	8-7/8"	12	6
G30102	2"	11-1/4"	8-7/8"	12	7
G14025	2-1/2"	11-1/4"	8-7/8"	12	8
G30103	3"	13-1/4"	9-7/8"	12	9
G30104	4"	14"	11-1/2"	12	13