

GooseNeck Floods



GOOSENECK



30W - Stationary Head



25W & 42W - Swivel Head

- 120-277V
- CRI: 80
- IP65 Outdoor Wet Location Rated
- Aluminum Housing,
- Clear Polycarbonate Lens
- Includes Photocell
- Swivel Head - 25W & 42W
- Color Temperature: 5000K
- Operating temp: -22°F To 158°F
- 4000V Surge Suppression
- 5 Year Warranty

Cat. No.	Color	Color Temp	Watts	Delivered Lumens	Replaces Metal Halide	Dimensions (Inches)			Weight (lbs)	Case Qty
						Length	Diameter	Height		

25W 10" Diameter

75100	Black	3000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75101	Bronze	3000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75102	White	3000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75103	Black	4000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75104	Bronze	4000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75105	White	4000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75106	Black	5000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75107	Bronze	5000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1
75108	White	5000K	25	2,287	75W	13-3/4"	10"	20-3/4"	4	1

30W 10" Diameter

75109	Black	3000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75110	Bronze	3000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75111	White	3000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75112	Black	4000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75113	Bronze	4000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75114	White	4000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75115	Black	5000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75116	Bronze	5000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1
75117	White	5000K	30	3,018	100	16-3/4"	9-3/8"	8-5/8"	3	1

42W 14" Diameter

75118	Black	3000K	42	3,812	150	15"	14"	24"	4	1
75119	Bronze	3000K	42	3,812	150	15"	14"	24"	4	1
75120	White	3000K	42	3,812	150	15"	14"	24"	4	1
75121	Black	4000K	42	3,812	150	15"	14"	24"	4	1
75122	Bronze	4000K	42	3,812	150	15"	14"	24"	4	1
75123	White	4000K	42	3,812	150	15"	14"	24"	4	1
75124	Black	5000K	42	3,812	150	15"	14"	24"	4	1
75125	Bronze	5000K	42	3,812	150	15"	14"	24"	4	1
75126	White	5000K	42	3,812	150	15"	14"	24"	4	1