

Air Conditioner Disconnects



Air Conditioner Disconnects

30 & 60 Amp | Fusible and Non-Fusible



U3832



U3802

Milbank's air conditioner disconnects have a removable hinged cover which makes wiring a breeze. Our compact design meets all wire bending space requirements in the NEC and complies with article 440-14 in the NEC. To ensure the safest conditions, we designed our disconnect pullers to be removable, or they may be reinstalled in the off position. Another safety feature is the padlock provision on the front cover. As with all Milbank products, our enclosure is constructed of G90U galvanized steel and finished with an attractive, light gray, baked powder coating. Our advanced finish combines epoxy and polyester hybrid resins into a hybrid powder coating which is then electrostatically applied. This offers a durable, nonfading finish.

30-60 Amp — 1Ø 240 VAC — Air Conditioner Disconnects

Catalog Number	Amp	Type	Max H.P.	Weight (lbs.)	Line/Load Wire Range		Ground Wire Range CU/AL	Dimensions			Wire Rating	
					CU	AL		D"	W"	H"	CU °C	AL °C
U3802	60	Non-Fusible	10	3.25	#14-#2	#12-#2	#14-4	2½	5	7½	60°/75°	60°/75°
U3832	30	Fusible	3	2.5	#14-#3	#14-#3	#14-3	2⅞	5	7	60°/75°	60°
U3862	60	Fusible	10	3.3	#14-#3	#14-#3	#14-3	2⅞	5	9	60°/75°	60°/75°

Notes

- UL listed as Enclosed Pullout Switch
- Type 3R rainproof
- One-inch concentric knockouts



Air Conditioner Disconnects

60 Amp



U3812

Specifications

- Manual switch
- UL/cUL listed
- Type 3R rainproof enclosure
- Duplex ground connector
- Six 1" concentric knockouts
- 1Ø, 240 VAC
- Standard package of 6
- Pad-lockable door
- Removable front cover and deadfront

60 Amp — 1Ø 240 VAC — Manual Switch — Air Conditioner Disconnect

Catalog Number	Amp	Type	Max H.P.	Weight (lbs.)	Line/Load Wire Range		Ground Wire Range CU/AL	Dimensions			Wire Rating	
					CU	AL		D"	W"	H"	CU °C	AL °C
U3812	60	Non-Auto	10	3.25	#14-#2	#12-#2	#14-4	2½	5	7½	60°/75°	60°/75°



U3822-20GWR

Specifications

- Meets NEC #210.63 requirements
- UL listed as Power Outlet
- Type 3R enclosure
- In-use cover
- Duplex ground connector
- 1" concentric knockouts
- 1Ø, 240 volt
- 60 amp, non-fused
- 20 amp GFCI receptacle
- Reset/test button
- Weather and tamper resistant
- Meets NEC #406.8 requirements

60 Amp — 1Ø, 240 VAC — Air Conditioner Disconnect with 20A GFCI Receptacle

Catalog Number	Amp	Type	Max H.P.	Weight (lbs.)	Line/Load Wire Range		Ground Wire Range CU/AL	Dimensions			Wire Rating	
					CU	AL		D"	W"	H"	CU °C	AL °C
U3822-20GWR	60	Non-Fusible	10	6	#14-#2	#12-#2	#14-4	4⅞	5¼	7⅞	60°/75°	60°/75°

50 Amp Spa Box with GFCI Protection

For use as Hot Tub Disconnect or Sub Panel Enclosure



U4881-O-50GB

Specifications

- 240 volt ground fault protection
- UL listed, Type 3R rainproof
- 2-pole, 50 amp GFCI breaker protection
- Compact size
- Three or four wire installation
- 1Ø, 120/240 VAC
- Standard package of 12
- Two extra one-pole breaker spaces
- 100 amp overall rating
- Easy to install

Milbank's sub-panel enclosure has a compact design that meets NEC wire bending space requirements and complies with Article 680-42 in the NEC for GFCI protection. All units are designed with a padlock provision on the cover for security. This enclosure is constructed of G90 galvanized steel and finished with an attractive, light gray baked powder coating. Our advanced finish combines epoxy and polyester hybrid resins into a powder coating which is then electrostatically applied. This offers a durable, nonfading finish. Type 3R design allows use in indoor and outdoor applications.

Hot Tub Disconnect or Sub Panel Breaker Enclosure — Type 3R

Catalog Number	Amp	Type	Weight (lbs.)	Line/Load Wire Range		Ground Wire Range CU/AL	Dimensions		
				CU	AL		D"	W"	H"
U4881-O	—	Breaker Provision	7	#14-1/0	#14-1/0	#14-1/0	3¾	7½	8½
U4881-O-50GB	50	Breaker	8	#14-1/0	#14-1/0	#14-1/0	3¾	7½	8½
U4881-O-60GB	60	Breaker	8	#14-1/0	#14-1/0	#14-1/0	3¾	7½	8½