


SQUARE RECESSED RETROFIT DOWNLIGHT 6" 15W










Part#	Housing Color	Wattage	Lumens	сст	Voltage	Input Current @ 120V	Lumens/ Watt	Energy Star
72635	White	15W	971	3000K	120	.128A	65	Yes

PHOTOMETRY



Maximum Candela = 289.05 Located At Horizontal Angle = 180, Vertical Angle = 1 # 1 - Vertical Plane Through Horizontal Angles (180 - 0) (Through Max. Cd.)

www.morrisproducts.com



Frequency: 60Hz

50,000+ LED Life Span

Beam Angle: 107°

15 Watts

SQUARE RECESSED RETROFIT DOWNLIGHT 6" 15W

Construction:

White Finish

Technical Specifications:

Electrical: Operating Temperature:

Input Voltage: 120 Minimum Starting -31° - 122° F

Current: .128A @ 120V

Power Factor: ≥.97 Housing: Aluminum Housing/Trim

Product Parameters: IP Rating: IP44 Wet Indoor Location Rated

Efficacy: 65 lumens per watt

Lens Material: Frosted Polycarbonate Lens

CCT: 3000k (Warm White)

Mounting: Retrofit Screw In Base

Chromacity Measurements: Listings: ETL, Energy Star

BUG Rating: N/A
CRI: ≥ 90 Carton Qty: 12

R9: 37 Weight: 1.4 lb

Chromaticity (x,y): x=.4404; y= .3977 Warranty:

Chromaticity (u,v): u=.2554; v= .3462

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).

Component Specifications:

LED: Luxeon 3030 2D
Driver: 120V 50-60HZ
Driver Output Volts:
Driver Output Amps:
Surge Protection:

Dimming: Triac Dimming