

LED Photocells



LED Button Style Photocells



- LED Compatible
- Silicon Light Sensor/IR Filtered
- Zero Cross/DC Relay for attenuation of In-Rush Current
- MCU Circuitry - Conformal Coated PCB
- MOV Surge Suppression
- 5 Second Time Delay
- Polycarbonate Housing
- IP65 Outdoor Rated
- Operating temp: -22F To 158F
- 1 Year Warranty

Cat. No.	Mounting	Volts	On/Off Lux	Tungsten Watts	Ballast VA	Amps	Case Qty
39100	Fixture	120-277	16 Lx/24 Lx	1000	1200@ 120V 1800@ 208-277V	8A @ 120V 5A @ 208-277V	160
39101	Wall Plate	120-277	16 Lx/24 Lx	1000	1200@ 120V 1800@ 208-277V	8A @ 120V 5A @ 208-277V	100

LED Shutter Style Photocells



- LED Compatible
- Silicon Light Sensor/IR Filtered
- Zero Cross/DC Relay for attenuation of In-Rush Current
- MCU Circuitry - Conformal Coated PCB
- MOV Surge Suppression
- 5 Second Time Delay
- Polycarbonate Housing
- IP65 Outdoor Rated
- Operating temp: -22F To 158F
- 1 Year Warranty

Cat. No.	Mounting	Volts	On/Off Lux	Tungsten Watts	Ballast VA	Amps	Case Qty
39102	Fixed	120-277	16 Lx/24 Lx	1000	1200@ 120V 1800@ 208-277V	8A @ 120V 5A @ 208-277V	200
39103	Swivel	120-277	16 Lx/24 Lx	1000	1200@ 120V 1800@ 208-277V	8A @ 120V 5A @ 208-277V	100

LED Pencil Style Photocells



- LED Compatible
- Silicon Light Sensor/IR Filtered
- Zero Cross/DC Relay for attenuation of In-Rush Current
- MCU Circuitry - Conformal Coated PCB
- MOV Surge Suppression
- 5 Second Time Delay
- Polycarbonate Housing
- IP65 Outdoor Rated
- Operating temp: -22F To 158F
- 1 Year Warranty

Cat. No.	Mounting	Volts	On/Off Lux	Tungsten Watts	Ballast VA	Amps	Case Qty
39104	Swivel	120-277	16 Lx/24 Lx	1000	1200@ 120V 1800@ 208-277V	8A @ 120V 5A @ 208-277V	200

LED Twist-Lock Style Photocells



- LED Compatible
- Silicon Light Sensor/IR Filtered
- Zero Cross/DC Relay for attenuation of In-Rush Current
- MCU Circuitry - Conformal Coated PCB
- MOV Surge Suppression
- Delay On: 0-10 Second
- Delay Off: 5-20 Second
- Midnight Off
- Fail On
- IR Filtered Photodiode
- Polycarbonate Housing
- IP65 Outdoor Rated
- Operating temp: -40F To 158F
- 1 Year Warranty

Cat. No.	Mounting	Volts	On/Off Lux	Tungsten Watts	Ballast VA	Amps	Case Qty
39106	Twist Lock	120-277	16 Lx/24 Lx	1000	1800 @ 120V 1800 @ 208-277V	8A @ 120V 5A @ 208-277V	100
39107	Twist Lock	480	16 Lx/24 Lx	1800	1800	5A	100